

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P583084

Luminaire Tested: **HC655D010-HM64560930-61NDC**

Issue Date: 9/16/2021

**Test Information**

Test Method: LM-41-14  
Report Number: P583084  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2105-241-1)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 9/16/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: HALO COMMERCIAL  
Catalog Number: HC655D010-HM64560930-61NDC  
Description: HALO COMMERCIAL 6" ROUND, NEW CONSTRUCTION FRAME, WITH 6" NARROW DISTRIBUTION, SPECULAR TRIM  
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 5117.0 lumens  
Efficiency: N/A  
Efficacy: 98.4 lumens/watt  
Spacing Criteria (0/90/45): 0.93 / 0.93 / 0.88  
Luminous Opening: Circular (Dia: 0.5' x H: 0')  
CIE Type: Direct


Input Watts (W): 52  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P583084

CATALOG NUMBER: HC655D010-HM64560930-61NDC

### Luminous Intensity Polar Plot





TEST NUMBER: P583084

CATALOG NUMBER: HC655D010-HM64560930-61NDC

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	114	111	108	106	111	109	107	105	105	103	101	101	100	98	98	97	96	94			94
2	108	103	99	96	106	102	98	95	98	96	93	96	93	91	93	91	89	87			87
3	103	97	92	88	101	95	91	87	93	89	86	90	87	84	88	85	83	82			82
4	98	90	85	81	96	89	84	80	87	83	79	85	81	79	83	80	78	76			76
5	93	85	79	75	91	84	79	75	82	77	74	80	76	73	79	75	73	71			71
6	88	80	74	70	87	79	73	69	77	73	69	76	72	68	75	71	68	67			67
7	84	75	69	65	83	74	69	65	73	68	64	72	67	64	71	67	64	62			62
8	80	71	65	61	79	70	65	61	69	64	60	68	64	60	67	63	60	59			59
9	76	67	61	57	75	66	61	57	65	60	57	65	60	57	64	60	56	55			55
10	73	63	58	54	72	63	57	54	62	57	54	61	57	53	61	56	53	52			52

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	305595
5°	306207
10°	311245
15°	313515
20°	286587
25°	225194
30°	164842
35°	116935
40°	55311
45°	21103
50°	9450
55°	2571
60°	1107
65°	869
70°	529
75°	699
80°	0
85°	0



TEST NUMBER: P583084

CATALOG NUMBER: HC655D010-HM64560930-61NDC

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	532.3	10.4
10°-20°	1526.8	29.8
20°-30°	1698.3	33.2
30°-40°	1060.9	20.7
40°-50°	252.1	4.9
50°-60°	36.1	0.7
60°-70°	7.5	0.1
70°-80°	3.0	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3757.4	73.4
0°-40°	4818.4	94.2
0°-60°	5106.5	99.8
0°-90°	5117.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5117.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	5574	
5°	5564	532
15°	5524	1527
25°	3723	1698
35°	1747	1061
45°	272	252
55°	27	36
65°	7	7
75°	3	3
85°	0	0
90°	0	



TEST NUMBER: P583084

CATALOG NUMBER: HC655D010-HM64560930-61NDC

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	5574.5
2.5°	5551.0
5°	5564.4
7.5°	5584.6
10°	5591.3
12.5°	5587.9
15°	5524.1
17.5°	5309.1
20°	4912.5
22.5°	4354.7
25°	3723.0
27.5°	3118.3
30°	2604.1
32.5°	2177.4
35°	1747.3
37.5°	1283.6
40°	772.9
42.5°	446.9
45°	272.2
47.5°	174.7
50°	110.8
52.5°	63.9
55°	26.9
57.5°	13.5
60°	10.1
62.5°	10.1
65°	6.7
67.5°	6.7
70°	3.3
72.5°	3.3
75°	3.3
77.5°	3.3
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P







— 0°-180°







(END OF REPORT)