

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P584168

Luminaire Tested: **HC825D010-HM82555927-81MDH**

Issue Date: 10/21/2021

Test Information

Test Method: LM-41-14
Report Number: P584168
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2109-368-5)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 10/21/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC825D010-HM82555927-81MDH
Description: HALO COMMERCIAL 8" ROUND, NEW CONSTRUCTION FRAME, WITH 8" MEDIUM DISTRIBUTION, HAZE TRIM
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1966.5 lumens
Efficiency: N/A
Efficacy: 73.4 lumens/watt
Spacing Criteria (0/90/45): 0.68 / 0.68 / 0.81
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 26.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P584168

CATALOG NUMBER: HC825D010-HM82555927-81MDH

Luminous Intensity Polar Plot





TEST NUMBER: P584168

CATALOG NUMBER: HC825D010-HM82555927-81MDH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	94			
2	108	103	99	96	106	101	98	95	98	95	93	95	93	91	92	90	89	87			
3	103	96	91	87	101	95	90	87	92	88	85	90	87	84	88	85	83	81			
4	97	90	85	80	96	89	84	80	87	82	79	85	81	78	83	80	77	76			
5	93	84	79	74	91	83	78	74	82	77	73	80	76	73	78	75	72	71			
6	88	79	73	69	87	78	73	69	77	72	68	76	71	68	74	70	67	66			
7	84	75	69	64	82	74	68	64	73	68	64	71	67	64	70	66	63	62			
8	80	70	64	60	79	70	64	60	69	64	60	68	63	60	67	63	60	58			
9	76	67	61	57	75	66	61	57	65	60	56	64	60	56	63	59	56	55			
10	73	63	57	54	72	63	57	53	62	57	53	61	56	53	60	56	53	52			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	89934
5°	81954
10°	70023
15°	61064
20°	54427
25°	48280
30°	39527
35°	22703
40°	10076
45°	5861
50°	3382
55°	1935
60°	1067
65°	679
70°	487
75°	322
80°	231
85°	460



TEST NUMBER: P584168

CATALOG NUMBER: HC825D010-HM82555927-81MDH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	239.7	12.2
10°-20°	537.7	27.3
20°-30°	643.6	32.7
30°-40°	389.4	19.8
40°-50°	109.1	5.5
50°-60°	33.9	1.7
60°-70°	9.7	0.5
70°-80°	2.6	0.1
80°-90°	0.9	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1421.0	72.3
0°-40°	1810.3	92.1
0°-60°	1953.3	99.3
0°-90°	1966.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1966.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2916	
5°	2648	240
15°	1913	538
25°	1419	644
35°	603	389
45°	134	109
55°	36	34
65°	9	10
75°	3	3
85°	1	1
90°	0	



TEST NUMBER: P584168

CATALOG NUMBER: HC825D010-HM82555927-81MDH

CANDELA DISTRIBUTION (FULL):

	0°
0°	2916.5
2.5°	2834.0
5°	2647.6
7.5°	2437.2
10°	2236.3
12.5°	2060.6
15°	1912.8
17.5°	1782.4
20°	1658.6
22.5°	1544.1
25°	1419.0
27.5°	1277.9
30°	1110.1
32.5°	893.2
35°	603.1
37.5°	375.4
40°	250.3
42.5°	179.7
45°	134.4
47.5°	98.5
50°	70.5
52.5°	49.2
55°	36.0
57.5°	24.0
60°	17.3
62.5°	12.0
65°	9.3
67.5°	6.6
70°	5.4
72.5°	2.7
75°	2.7
77.5°	1.3
80°	1.3
82.5°	1.3
85°	1.3
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







(END OF REPORT)