

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P584970

Luminaire Tested: **HC855D010-HM82555840-81NDH**

Issue Date: 10/21/2021

Test Information

Test Method: LM-41-14
Report Number: P584970
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2109-368-2)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 10/21/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC855D010-HM82555840-81NDH
Description: HALO COMMERCIAL 8" ROUND, NEW CONSTRUCTION FRAME, WITH 8" NARROW DISTRIBUTION, HAZE TRIM
Light Source: (1) HIGH LUMEN LED 80CRI / 4000K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5511.8 lumens
Efficiency: N/A
Efficacy: 106.0 lumens/watt
Spacing Criteria (0/90/45): 0.42 / 0.42 / 0.57
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 52
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P584970

CATALOG NUMBER: HC855D010-HM82555840-81NDH

Luminous Intensity Polar Plot





TEST NUMBER: P584970

CATALOG NUMBER: HC855D010-HM82555840-81NDH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	114	112	109	107	112	109	107	106	105	104	102	102	100	99	98	97	96	95	95	95	95
2	109	105	101	98	107	103	100	97	100	97	95	97	95	93	94	92	91	89	89	89	89
3	104	99	94	91	102	97	93	90	95	91	88	92	90	87	90	88	86	84	84	84	84
4	100	93	88	84	98	92	87	84	90	86	83	88	85	82	86	83	81	80	80	80	80
5	96	88	83	79	94	87	82	79	86	81	78	84	80	77	82	79	77	75	75	75	75
6	92	84	78	75	90	83	78	74	81	77	74	80	76	73	79	76	73	72	72	72	72
7	88	80	74	70	87	79	74	70	78	73	70	77	73	70	76	72	69	68	68	68	68
8	84	76	71	67	83	75	70	67	74	70	66	73	69	66	72	69	66	65	65	65	65
9	81	72	67	64	80	72	67	63	71	66	63	70	66	63	69	66	63	62	62	62	62
10	78	69	64	61	77	69	64	61	68	63	60	67	63	60	67	63	60	59	59	59	59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	438569
5°	371558
10°	269584
15°	202450
20°	159738
25°	128849
30°	95479
35°	38683
40°	16315
45°	8748
50°	3929
55°	1978
60°	1264
65°	897
70°	739
75°	488
80°	728
85°	1451



TEST NUMBER: P584970

CATALOG NUMBER: HC855D010-HM82555840-81NDH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1030.6	18.7
10°-20°	1781.1	32.3
20°-30°	1722.1	31.2
30°-40°	756.4	13.7
40°-50°	163.5	3.0
50°-60°	36.7	0.7
60°-70°	12.6	0.2
70°-80°	4.9	0.1
80°-90°	3.9	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4533.8	82.3
0°-40°	5290.2	96.0
0°-60°	5490.4	99.6
0°-90°	5511.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5511.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	14222	
5°	12004	###
15°	6342	1781
25°	3787	1722
35°	1028	756
45°	201	163
55°	37	37
65°	12	13
75°	4	5
85°	4	4
90°	0	



TEST NUMBER: P584970

CATALOG NUMBER: HC855D010-HM82555840-81NDH

CANDELA DISTRIBUTION (FULL):

	0°
0°	14222.5
1°	14116.0
2°	13825.4
3°	13301.3
4°	12674.9
5°	12003.5
6°	11270.7
7°	10533.8
8°	9841.9
9°	9199.1
10°	8609.6
11°	8052.8
12°	7553.4
13°	7098.9
14°	6697.7
15°	6341.6
17.5°	5543.2
20°	4867.8
22.5°	4274.0
25°	3787.0
27.5°	3291.6
30°	2681.5
32.5°	1821.9
35°	1027.6
37.5°	605.9
40°	405.3
42.5°	286.6
45°	200.6
47.5°	131.0
50°	81.9
52.5°	49.1
55°	36.8
57.5°	28.7
60°	20.5
62.5°	16.4
65°	12.3
67.5°	8.2
70°	8.2
72.5°	4.1
75°	4.1
77.5°	4.1
80°	4.1
82.5°	4.1



TEST NUMBER: P584970

CATALOG NUMBER: HC855D010-HM82555840-81NDH

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







85°	4.1
87.5°	4.1



(END OF REPORT)