

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P583570

Luminaire Tested: **HC807D010-HM80520827-81WDH**

Issue Date: 10/21/2021

Test Information

Test Method: LM-41-14
Report Number: P583570
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2109-368-8)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 10/21/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC807D010-HM80520827-81WDH
Description: HALO COMMERCIAL 8" ROUND, NEW CONSTRUCTION FRAME, WITH 8" WIDE DISTRIBUTION, HAZE TRIM
Light Source: (1) HIGH LUMEN LED 80CRI / 2700K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 995.7 lumens
Efficiency: N/A
Efficacy: 124.5 lumens/watt
Spacing Criteria (0/90/45): 1.12 / 1.12 / 1.06
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P583570

CATALOG NUMBER: HC807D010-HM80520827-81WDH

Luminous Intensity Polar Plot





TEST NUMBER: P583570

CATALOG NUMBER: HC807D010-HM80520827-81WDH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	109	107	104	110	107	105	102	103	101	99	99	98	96	96	95	93	92			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83			
3	99	92	86	81	97	90	85	81	88	83	79	85	81	78	83	80	77	75			
4	93	84	78	73	91	83	77	72	81	76	72	79	74	71	77	73	70	68			
5	87	78	71	66	86	77	70	66	75	69	65	73	68	64	71	67	64	62			
6	82	72	65	60	80	71	64	60	69	64	59	68	63	59	66	62	58	57			
7	77	67	60	55	76	66	59	55	64	59	54	63	58	54	62	57	54	52			
8	73	62	55	50	71	61	55	50	60	54	50	59	54	50	58	53	49	48			
9	69	58	51	46	67	57	51	46	56	50	46	55	50	46	54	49	46	44			
10	65	54	47	43	64	53	47	43	53	47	43	52	46	43	51	46	42	41			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	22794
5°	22284
10°	21602
15°	21162
20°	20972
25°	20659
30°	19569
35°	16259
40°	9576
45°	6332
50°	4989
55°	3667
60°	2547
65°	1554
70°	676
75°	298
80°	213
85°	0



TEST NUMBER: P583570

CATALOG NUMBER: HC807D010-HM80520827-81WDH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	67.8	6.8
10°-20°	187.4	18.8
20°-30°	277.7	27.9
30°-40°	256.6	25.8
40°-50°	118.3	11.9
50°-60°	62.2	6.2
60°-70°	22.0	2.2
70°-80°	3.5	0.3
80°-90°	0.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	532.9	53.5
0°-40°	789.4	79.3
0°-60°	969.9	97.4
0°-90°	995.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	995.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	739	
5°	720	68
15°	663	187
25°	607	278
35°	432	257
45°	145	118
55°	68	62
65°	21	22
75°	2	3
85°	0	0
90°	0	



TEST NUMBER: P583570

CATALOG NUMBER: HC807D010-HM80520827-81WDH

CANDELA DISTRIBUTION (FULL):

	0°
0°	739.2
2.5°	733.0
5°	719.9
7.5°	705.5
10°	689.9
12.5°	674.8
15°	662.9
17.5°	652.2
20°	639.1
22.5°	624.7
25°	607.2
27.5°	583.4
30°	549.6
32.5°	501.4
35°	431.9
37.5°	331.7
40°	237.9
42.5°	178.4
45°	145.2
47.5°	123.3
50°	104.0
52.5°	85.1
55°	68.2
57.5°	53.8
60°	41.3
62.5°	31.3
65°	21.3
67.5°	12.5
70°	7.5
72.5°	4.4
75°	2.5
77.5°	1.9
80°	1.2
82.5°	0.6
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







(END OF REPORT)