

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P593499

Luminaire Tested: **HC807D010-HM80520950-81WDBB**

Issue Date: 10/21/2021

Test Information

Test Method: LM-41-14
Report Number: P593499
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2109-368-11)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 10/21/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC807D010-HM80520950-81WDBB
Description: HALO COMMERCIAL 8" ROUND, NEW CONSTRUCTION FRAME, WITH 8" WIDE DISTRIBUTION, BLACK BAFFLE TRIM
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 916.7 lumens
Efficiency: N/A
Efficacy: 114.6 lumens/watt
Spacing Criteria (0/90/45): 1.32 / 1.32 / 1.13
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P593499

CATALOG NUMBER: HC807D010-HM80520950-81WDBB

Luminous Intensity Polar Plot





TEST NUMBER: P593499

CATALOG NUMBER: HC807D010-HM80520950-81WDBB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	109	107	104	110	107	105	102	103	101	99	99	98	96	96	95	93	92			
2	106	100	95	92	104	98	94	91	95	92	89	92	89	87	89	87	85	83			
3	99	92	86	81	97	90	85	81	88	83	79	85	81	78	83	80	77	75			
4	93	84	78	73	91	83	77	72	81	76	71	79	74	71	77	73	70	68			
5	87	77	71	66	85	76	70	65	74	69	65	73	68	64	71	67	63	62			
6	82	71	64	59	80	70	64	59	69	63	59	67	62	58	66	61	58	56			
7	77	66	59	54	75	65	59	54	64	58	54	63	57	53	61	57	53	51			
8	72	61	54	49	71	61	54	49	59	53	49	58	53	49	57	52	49	47			
9	68	57	50	45	67	56	50	45	55	49	45	54	49	45	53	48	45	43			
10	64	53	46	42	63	53	46	42	52	46	42	51	45	42	50	45	41	40			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	17176
5°	17034
10°	16808
15°	17000
20°	18360
25°	20078
30°	19833
35°	16451
40°	9685
45°	6328
50°	4903
55°	3258
60°	1585
65°	489
70°	162
75°	143
80°	107
85°	212



TEST NUMBER: P593499

CATALOG NUMBER: HC807D010-HM80520950-81WDBB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	52.1	5.7
10°-20°	153.0	16.7
20°-30°	267.5	29.2
30°-40°	260.2	28.4
40°-50°	118.3	12.9
50°-60°	54.9	6.0
60°-70°	9.2	1.0
70°-80°	1.1	0.1
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	472.6	51.6
0°-40°	732.8	79.9
0°-60°	906.0	98.8
0°-90°	916.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	916.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	557	
5°	550	52
15°	532	153
25°	590	267
35°	437	260
45°	145	118
55°	61	55
65°	7	9
75°	1	1
85°	1	0
90°	0	



TEST NUMBER: P593499

CATALOG NUMBER: HC807D010-HM80520950-81WDBB

CANDELA DISTRIBUTION (FULL):

	0°
0°	557.0
2.5°	555.8
5°	550.3
7.5°	544.2
10°	536.8
12.5°	531.3
15°	532.5
17.5°	542.3
20°	559.5
22.5°	579.0
25°	590.1
27.5°	583.9
30°	557.0
32.5°	509.9
35°	437.0
37.5°	336.6
40°	240.6
42.5°	179.4
45°	145.1
47.5°	122.4
50°	102.2
52.5°	81.4
55°	60.6
57.5°	41.6
60°	25.7
62.5°	14.1
65°	6.7
67.5°	3.1
70°	1.8
72.5°	1.2
75°	1.2
77.5°	0.6
80°	0.6
82.5°	0.6
85°	0.6
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







(END OF REPORT)