

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P579901

Luminaire Tested: **HCC4W15D010MW-HM40525927-41WDWB**

Issue Date: 9/9/2021

**Test Information**

Test Method: LM-41-14  
Report Number: P579901  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2106-266-10)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 9/9/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: HALO COMMERCIAL  
Catalog Number: HCC4W15D010MW-HM40525927-41WDWB  
Description: HALO COMMERCIAL 4" ROUND, NEW CONSTRUCTION FRAME, WITH 4" WIDE DISTRIBUTION, WHITE BAFFLE TRIM  
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT CYLINDER  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 1227.8 lumens  
Efficiency: N/A  
Efficacy: 87.7 lumens/watt  
Spacing Criteria (0/90/45): 1.14 / 1.14 / 1.07  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct

Input Watts (W): 14  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P579901  
CATALOG NUMBER: HCC4W15D010MW-HM40525927-41WDWB

### Luminous Intensity Polar Plot





TEST NUMBER: P579901  
 CATALOG NUMBER: HCC4W15D010MW-HM40525927-41WDWB

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100	
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	92	90			90	
2	104	98	93	89	102	96	92	88	93	89	86	90	87	84	87	84	82	80			80	
3	98	89	83	78	95	88	82	78	85	80	76	83	78	75	80	77	74	72			72	
4	91	82	75	70	89	81	74	69	78	73	69	76	72	68	74	70	67	65			65	
5	86	75	68	63	84	74	68	63	72	67	62	71	65	61	69	64	61	59			59	
6	80	70	62	57	79	69	62	57	67	61	57	66	60	56	64	59	56	54			54	
7	76	64	57	52	74	64	57	52	62	56	52	61	56	51	60	55	51	49			49	
8	71	60	53	48	70	59	53	48	58	52	48	57	51	47	56	51	47	46			46	
9	67	56	49	44	66	55	49	44	54	48	44	53	48	44	52	47	44	42			42	
10	64	52	46	41	62	52	45	41	51	45	41	50	45	41	49	44	41	39			39	

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	100810
5°	101282
10°	101977
15°	103000
20°	101282
25°	96615
30°	87792
35°	70816
40°	49142
45°	32253
50°	21607
55°	15376
60°	13124
65°	15089
70°	16193
75°	15584
80°	14064
85°	12879



TEST NUMBER: P579901  
 CATALOG NUMBER: HCC4W15D010MW-HM40525927-41WDWB

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	78.0	6.3
10°-20°	226.6	18.5
20°-30°	323.7	26.4
30°-40°	289.2	23.6
40°-50°	148.3	12.1
50°-60°	67.4	5.5
60°-70°	50.3	4.1
70°-80°	34.2	2.8
80°-90°	10.1	0.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	628.3	51.2
0°-40°	917.5	74.7
0°-60°	1133.2	92.3
0°-90°	1227.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1227.8	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	817	
5°	818	78
15°	807	227
25°	710	324
35°	470	289
45°	185	148
55°	72	67
65°	52	50
75°	33	34
85°	9	10
90°	0	



TEST NUMBER: P579901  
CATALOG NUMBER: HCC4W15D010MW-HM40525927-41WDWB

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	817.3
2.5°	814.2
5°	818.0
7.5°	818.0
10°	814.2
12.5°	810.3
15°	806.6
17.5°	795.1
20°	771.6
22.5°	742.7
25°	709.9
27.5°	668.9
30°	616.4
32.5°	549.4
35°	470.3
37.5°	385.8
40°	305.2
42.5°	238.2
45°	184.9
47.5°	144.6
50°	112.6
52.5°	88.2
55°	71.5
57.5°	60.1
60°	53.2
62.5°	51.7
65°	51.7
67.5°	50.3
70°	44.9
72.5°	38.8
75°	32.7
77.5°	25.9
80°	19.8
82.5°	14.4
85°	9.1
87.5°	3.8
90°	0.0

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)