

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P580339

Luminaire Tested: **HCC4W30D010MB-HM43040927-41WDW**

Issue Date: 9/9/2021

Test Information

Test Method: LM-41-14
Report Number: P580339
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2106-266-9)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/9/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HCC4W30D010MB-HM43040927-41WDW
Description: HALO COMMERCIAL 4" ROUND, NEW CONSTRUCTION FRAME, WITH 4" WIDE DISTRIBUTION, WHITE TRIM
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
CYLINDER
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2335.1 lumens
Efficiency: N/A
Efficacy: 83.4 lumens/watt
Spacing Criteria (0/90/45): 1.06 / 1.07 / 1.04
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 28
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P580339
CATALOG NUMBER: HCC4W30D010MB-HM43040927-41WDW

Luminous Intensity Polar Plot





TEST NUMBER: P580339

CATALOG NUMBER: HCC4W30D010MB-HM43040927-41WDW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100					100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	94	92	90	89					89			
2	103	97	91	87	101	95	90	86	91	87	84	88	85	82	85	83	80	78					78			
3	96	87	81	76	94	86	80	75	83	78	74	81	76	72	78	74	71	69					69			
4	90	80	72	67	87	78	72	66	76	70	66	74	69	65	72	67	64	62					62			
5	84	73	65	60	82	72	65	59	70	64	59	68	63	58	66	62	58	56					56			
6	78	67	59	54	77	66	59	54	64	58	53	63	57	53	61	56	53	51					51			
7	73	62	54	49	72	61	54	49	60	53	49	58	53	48	57	52	48	46					46			
8	69	57	50	45	68	57	50	45	55	49	45	54	49	44	53	48	44	42					42			
9	65	53	46	41	64	53	46	41	52	45	41	51	45	41	50	45	41	39					39			
10	61	50	43	38	60	49	43	38	48	42	38	48	42	38	47	42	38	36					36			

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	186671	186671	186671
5°	186233	186431	186431
10°	184065	184253	184065
15°	181866	181866	181866
20°	174394	174801	175011
25°	163126	163330	163752
30°	146173	146600	146600
35°	118655	119603	119844
40°	89557	90073	90298
45°	68589	68310	68310
50°	56512	56205	56205
55°	48514	48170	48170
60°	43294	42900	42900
65°	40685	40685	40685
70°	37867	37867	37867
75°	34361	35123	34361
80°	32320	31183	32320
85°	26606	26606	26606



TEST NUMBER: P580339
 CATALOG NUMBER: HCC4W30D010MB-HM43040927-41WDW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	142.6	6.1
10°-20°	399.1	17.1
20°-30°	548.3	23.5
30°-40°	493.1	21.1
40°-50°	311.5	13.3
50°-60°	203.4	8.7
60°-70°	137.8	5.9
70°-80°	77.6	3.3
80°-90°	21.8	0.9
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1090.0	46.7
0°-40°	1583.1	67.8
0°-60°	2097.9	89.8
0°-90°	2335.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2335.1	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1513	1513	1513	1513	1513	
5°	1504	1504	1506	1506	1506	143
15°	1424	1424	1424	1424	1424	399
25°	1199	1200	1200	1203	1203	547
35°	788	791	794	798	796	491
45°	393	392	392	392	392	312
55°	226	226	224	226	224	204
65°	139	139	139	139	139	138
75°	72	74	74	74	72	77
85°	19	19	19	19	19	22
90°	0	0	0	0	0	



TEST NUMBER: P580339

CATALOG NUMBER: HCC4W30D010MB-HM43040927-41WDW

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1513.4	1513.4	1513.4	1513.4	1513.4
2.5°	1505.7	1505.7	1505.7	1505.7	1505.7
5°	1504.1	1504.1	1505.7	1505.7	1505.7
7.5°	1493.1	1494.7	1494.7	1494.7	1494.7
10°	1469.6	1469.6	1471.1	1471.1	1469.6
12.5°	1447.7	1447.7	1447.7	1449.3	1447.7
15°	1424.2	1424.2	1424.2	1424.2	1424.2
17.5°	1383.5	1385.0	1385.0	1385.0	1385.0
20°	1328.6	1331.7	1331.7	1333.3	1333.3
22.5°	1266.0	1267.5	1269.1	1270.6	1269.1
25°	1198.6	1200.1	1200.1	1203.2	1203.2
27.5°	1120.2	1121.8	1125.0	1125.0	1125.0
30°	1026.3	1027.8	1029.3	1029.3	1029.3
32.5°	915.0	915.0	918.1	919.7	918.1
35°	788.0	791.2	794.3	797.5	795.9
37.5°	667.4	670.6	672.2	672.2	673.8
40°	556.2	559.4	559.4	562.4	560.8
42.5°	468.5	466.9	466.9	470.0	468.5
45°	393.2	391.6	391.6	391.6	391.6
47.5°	338.4	336.8	336.8	336.8	336.8
50°	294.5	292.9	292.9	292.9	292.9
52.5°	258.5	257.0	257.0	257.0	255.4
55°	225.6	225.6	224.0	225.6	224.0
57.5°	195.8	195.8	195.8	195.8	195.8
60°	175.5	173.9	173.9	173.9	173.9
62.5°	156.7	156.7	156.7	156.7	156.7
65°	139.4	139.4	139.4	139.4	139.4
67.5°	122.2	120.7	122.2	122.2	120.7
70°	105.0	103.4	105.0	105.0	105.0
72.5°	87.8	87.8	87.8	89.3	87.8
75°	72.1	73.7	73.7	73.7	72.1
77.5°	58.0	59.6	58.0	58.0	58.0
80°	45.5	43.9	43.9	43.9	45.5
82.5°	31.4	31.4	31.4	31.4	31.4
85°	18.8	18.8	18.8	18.8	18.8
87.5°	7.8	7.8	7.8	7.8	7.8
90°	0.0	0.0	0.0	0.0	0.0

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180° - - 45°-225° - - - - 90°-270°

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)