

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P580501

Luminaire Tested: **HCC4S35D010BZ-HM43040930-41WDW**

Issue Date: 9/9/2021

Test Information

Test Method: LM-41-14
Report Number: P580501
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2106-266-9)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/9/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HCC4S35D010BZ-HM43040930-41WDW
Description: HALO COMMERCIAL 4" ROUND, NEW CONSTRUCTION FRAME, WITH 4" WIDE DISTRIBUTION, WHITE TRIM
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
CYLINDER
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3001.8 lumens
Efficiency: N/A
Efficacy: 89.1 lumens/watt
Spacing Criteria (0/90/45): 1.06 / 1.07 / 1.04
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 33.7
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P580501
CATALOG NUMBER: HCC4S35D010BZ-HM43040930-41WDW

Luminous Intensity Polar Plot





TEST NUMBER: P580501

CATALOG NUMBER: HCC4S35D010BZ-HM43040930-41WDW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	94	92	90	89			
2	103	97	91	87	101	95	90	86	91	87	84	88	85	82	85	83	80	78			
3	96	87	81	76	94	86	80	75	83	78	74	81	76	72	78	74	71	69			
4	90	80	72	67	87	78	72	66	76	70	66	74	69	65	72	68	64	62			
5	84	73	65	60	82	72	65	59	70	64	59	68	63	58	66	62	58	56			
6	78	67	59	54	77	66	59	54	64	58	53	63	57	53	61	56	53	51			
7	73	62	54	49	72	61	54	49	60	53	49	58	53	48	57	52	48	46			
8	69	57	50	45	68	57	50	45	55	49	45	54	49	44	53	48	44	42			
9	65	53	46	41	64	53	46	41	52	45	41	51	45	41	50	45	41	39			
10	61	50	43	38	60	49	43	38	48	42	38	48	42	38	47	42	38	36			

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	239969	239969	239969
5°	239387	239635	239635
10°	236607	236857	236607
15°	233787	233787	233787
20°	224182	224707	224969
25°	209684	209957	210501
30°	187876	188460	188460
35°	152550	153769	154056
40°	115127	115771	116093
45°	88178	87847	87847
50°	72669	72286	72286
55°	62363	61933	61933
60°	55654	55160	55160
65°	52331	52331	52331
70°	48686	48686	48686
75°	44130	45084	44130
80°	41483	40062	41483
85°	34249	34249	34249



TEST NUMBER: P580501
 CATALOG NUMBER: HCC4S35D010BZ-HM43040930-41WDW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	183.3	6.1
10°-20°	513.0	17.1
20°-30°	704.9	23.5
30°-40°	633.8	21.1
40°-50°	400.5	13.3
50°-60°	261.5	8.7
60°-70°	177.2	5.9
70°-80°	99.7	3.3
80°-90°	28.0	0.9
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1401.1	46.7
0°-40°	2034.9	67.8
0°-60°	2696.9	89.8
0°-90°	3001.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3001.8	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1946	1946	1946	1946	1946	
5°	1933	1933	1935	1935	1935	183
15°	1831	1831	1831	1831	1831	513
25°	1541	1543	1543	1547	1547	703
35°	1013	1017	1021	1025	1023	631
45°	506	504	504	504	504	401
55°	290	290	288	290	288	263
65°	179	179	179	179	179	178
75°	93	95	95	95	93	99
85°	24	24	24	24	24	28
90°	0	0	0	0	0	



TEST NUMBER: P580501

CATALOG NUMBER: HCC4S35D010BZ-HM43040930-41WDW

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1945.5	1945.5	1945.5	1945.5	1945.5
2.5°	1935.4	1935.4	1935.4	1935.4	1935.4
5°	1933.4	1933.4	1935.4	1935.4	1935.4
7.5°	1919.3	1921.4	1921.4	1921.4	1921.4
10°	1889.1	1889.1	1891.1	1891.1	1889.1
12.5°	1860.9	1860.9	1860.9	1862.9	1860.9
15°	1830.8	1830.8	1830.8	1830.8	1830.8
17.5°	1778.4	1780.4	1780.4	1780.4	1780.4
20°	1707.9	1711.9	1711.9	1713.9	1713.9
22.5°	1627.3	1629.4	1631.4	1633.4	1631.4
25°	1540.7	1542.7	1542.7	1546.7	1546.7
27.5°	1440.1	1442.0	1446.0	1446.0	1446.0
30°	1319.1	1321.1	1323.2	1323.2	1323.2
32.5°	1176.2	1176.2	1180.2	1182.2	1180.2
35°	1013.1	1017.1	1021.2	1025.1	1023.1
37.5°	857.9	862.0	864.0	864.0	866.0
40°	715.0	719.0	719.0	723.1	721.0
42.5°	602.2	600.2	600.2	604.2	602.2
45°	505.5	503.6	503.6	503.6	503.6
47.5°	435.0	433.0	433.0	433.0	433.0
50°	378.7	376.7	376.7	376.7	376.7
52.5°	332.4	330.3	330.3	330.3	328.3
55°	290.0	290.0	288.0	290.0	288.0
57.5°	251.8	251.8	251.8	251.8	251.8
60°	225.6	223.6	223.6	223.6	223.6
62.5°	201.4	201.4	201.4	201.4	201.4
65°	179.3	179.3	179.3	179.3	179.3
67.5°	157.1	155.1	157.1	157.1	155.1
70°	135.0	133.0	135.0	135.0	135.0
72.5°	112.7	112.7	112.7	114.8	112.7
75°	92.6	94.6	94.6	94.6	92.6
77.5°	74.5	76.5	74.5	74.5	74.5
80°	58.4	56.4	56.4	56.4	58.4
82.5°	40.2	40.2	40.2	40.2	40.2
85°	24.2	24.2	24.2	24.2	24.2
87.5°	10.1	10.1	10.1	10.1	10.1
90°	0.0	0.0	0.0	0.0	0.0

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180° - - 45°-225° - - - - 90°-270°

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)