

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P580514

Luminaire Tested: **HCC4W35D010MW-HM43040935-41NDC**

Issue Date: 9/9/2021

**Test Information**

Test Method: LM-41-14  
Report Number: P580514  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2106-266-1)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 9/9/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: HALO COMMERCIAL  
Catalog Number: HCC4W35D010MW-HM43040935-41NDC  
Description: HALO COMMERCIAL 4" ROUND, NEW CONSTRUCTION FRAME, WITH 4" NARROW DISTRIBUTION, SPECULAR TRIM  
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT  
CYLINDER  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 3109.9 lumens  
Efficiency: N/A  
Efficacy: 92.3 lumens/watt  
Spacing Criteria (0/90/45): 0.84 / 0.84 / 0.85  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct

Input Watts (W): 33.7  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P580514  
CATALOG NUMBER: HCC4W35D010MW-HM43040935-41NDC

### Luminous Intensity Polar Plot





TEST NUMBER: P580514

CATALOG NUMBER: HCC4W35D010MW-HM43040935-41NDC

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	114	111	108	106	111	109	106	104	105	103	101	101	100	98	97	96	95				94
2	108	103	99	96	106	101	98	95	98	95	93	95	93	91	93	91	89				87
3	103	96	91	87	101	95	90	87	92	88	85	90	87	84	88	85	83				81
4	97	90	85	80	96	89	84	80	87	82	79	85	81	78	83	80	77				76
5	93	84	79	74	91	83	78	74	82	77	73	80	76	73	78	75	72				71
6	88	79	73	69	87	78	73	69	77	72	68	75	71	68	74	70	67				66
7	84	75	69	64	82	74	68	64	73	68	64	71	67	64	70	66	63				62
8	80	70	64	60	78	70	64	60	69	64	60	68	63	60	67	62	59				58
9	76	66	61	57	75	66	60	57	65	60	56	64	59	56	63	59	56				55
10	72	63	57	53	71	62	57	53	62	57	53	61	56	53	60	56	53				51

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	458056
5°	457466
10°	448552
15°	417083
20°	358699
25°	288158
30°	224978
35°	157504
40°	80830
45°	41045
50°	20552
55°	7677
60°	3108
65°	2452
70°	1515
75°	1001
80°	1492
85°	0



TEST NUMBER: P580514  
 CATALOG NUMBER: HCC4W35D010MW-HM43040935-41NDC

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	349.3	11.2
10°-20°	901.6	29.0
20°-30°	971.3	31.2
30°-40°	638.1	20.5
40°-50°	198.4	6.4
50°-60°	38.9	1.3
60°-70°	8.3	0.3
70°-80°	3.0	0.1
80°-90°	0.9	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2222.2	71.5
0°-40°	2860.3	92.0
0°-60°	3097.7	99.6
0°-90°	3109.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3109.9	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3714	
5°	3695	349
15°	3266	902
25°	2117	971
35°	1046	638
45°	235	198
55°	36	39
65°	8	8
75°	2	3
85°	0	1
90°	0	



TEST NUMBER: P580514  
CATALOG NUMBER: HCC4W35D010MW-HM43040935-41NDC

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	3713.6
2.5°	3694.7
5°	3694.7
7.5°	3665.3
10°	3581.3
12.5°	3446.9
15°	3266.2
17.5°	3024.6
20°	2732.7
22.5°	2417.6
25°	2117.3
27.5°	1837.9
30°	1579.6
32.5°	1335.9
35°	1046.0
37.5°	728.8
40°	502.0
42.5°	346.5
45°	235.3
47.5°	159.6
50°	107.1
52.5°	67.2
55°	35.7
57.5°	14.7
60°	12.6
62.5°	10.5
65°	8.4
67.5°	6.3
70°	4.2
72.5°	4.2
75°	2.1
77.5°	2.1
80°	2.1
82.5°	2.1
85°	0.0
87.5°	0.0
90°	0.0

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)