

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P580582

Luminaire Tested: **HCC4S40D010BZ-HM43040835-41NDH**

Issue Date: 9/9/2021

**Test Information**

Test Method: LM-41-14  
Report Number: P580582  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2106-266-2)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 9/9/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: HALO COMMERCIAL  
Catalog Number: HCC4S40D010BZ-HM43040835-41NDH  
Description: HALO COMMERCIAL 4" ROUND, NEW CONSTRUCTION FRAME, WITH 4" NARROW DISTRIBUTION, HAZE TRIM  
Light Source: (1) HIGH LUMEN LED 80CRI / 3500K CCT  
CYLINDER  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 3783.7 lumens  
Efficiency: N/A  
Efficacy: 92.3 lumens/watt  
Spacing Criteria (0/90/45): 0.89 / 0.89 / 0.91  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct

Input Watts (W): 41  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P580582  
CATALOG NUMBER: HCC4S40D010BZ-HM43040835-41NDH

### Luminous Intensity Polar Plot





TEST NUMBER: P580582  
 CATALOG NUMBER: HCC4S40D010BZ-HM43040835-41NDH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97	96	95	93
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91	89	87	86
3	101	95	89	85	99	93	88	84	91	86	83		88	85	82		86	83	81	79
4	96	88	82	78	94	87	81	77	85	80	76		82	79	75		81	77	74	73
5	91	82	76	71	89	81	75	71	79	74	70		77	73	70		76	72	69	67
6	86	76	70	66	84	76	70	65	74	69	65		73	68	64		71	67	64	63
7	81	72	65	61	80	71	65	61	70	64	60		68	64	60		67	63	60	58
8	77	67	61	57	76	67	61	56	65	60	56		64	59	56		63	59	56	54
9	73	63	57	53	72	63	57	53	62	56	52		61	56	52		60	55	52	51
10	70	59	53	49	69	59	53	49	58	53	49		57	52	49		57	52	49	48

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	490755
5°	481845
10°	457032
15°	427337
20°	388101
25°	343440
30°	285666
35°	206005
40°	128572
45°	74153
50°	41832
55°	19935
60°	11422
65°	8727
70°	5914
75°	3908
80°	3907
85°	3821



TEST NUMBER: P580582  
 CATALOG NUMBER: HCC4S40D010BZ-HM43040835-41NDH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	363.7	9.6
10°-20°	933.5	24.7
20°-30°	1148.2	30.3
30°-40°	852.7	22.5
40°-50°	346.6	9.2
50°-60°	96.0	2.5
60°-70°	29.8	0.8
70°-80°	10.1	0.3
80°-90°	3.0	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2445.4	64.6
0°-40°	3298.2	87.2
0°-60°	3740.8	98.9
0°-90°	3783.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3783.7	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3979	
5°	3892	364
15°	3346	934
25°	2524	1148
35°	1368	853
45°	425	347
55°	93	96
65°	30	30
75°	8	10
85°	3	3
90°	0	



TEST NUMBER: P580582  
CATALOG NUMBER: HCC4S40D010BZ-HM43040835-41NDH

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	3978.7
2.5°	3940.5
5°	3891.6
7.5°	3793.4
10°	3649.0
12.5°	3499.1
15°	3346.5
17.5°	3163.9
20°	2956.7
22.5°	2746.9
25°	2523.5
27.5°	2280.9
30°	2005.7
32.5°	1692.3
35°	1368.1
37.5°	1062.8
40°	798.5
42.5°	583.1
45°	425.1
47.5°	305.2
50°	218.0
52.5°	149.9
55°	92.7
57.5°	60.0
60°	46.3
62.5°	38.1
65°	29.9
67.5°	21.7
70°	16.4
72.5°	13.7
75°	8.2
77.5°	5.5
80°	5.5
82.5°	2.7
85°	2.7
87.5°	2.7
90°	0.0

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)