

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P580627

Luminaire Tested: **HCC4W40D010MW-HM43040927-41WDW**

Issue Date: 9/9/2021

Test Information

Test Method: LM-41-14
Report Number: P580627
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2106-266-9)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/9/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HCC4W40D010MW-HM43040927-41WDW
Description: HALO COMMERCIAL 4" ROUND, NEW CONSTRUCTION FRAME, WITH 4" WIDE DISTRIBUTION, WHITE TRIM
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT CYLINDER
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3234.9 lumens
Efficiency: N/A
Efficacy: 78.9 lumens/watt
Spacing Criteria (0/90/45): 1.06 / 1.07 / 1.04
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 41
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P580627
CATALOG NUMBER: HCC4W40D010MW-HM43040927-41WDW

Luminous Intensity Polar Plot





TEST NUMBER: P580627

CATALOG NUMBER: HCC4W40D010MW-HM43040927-41WDW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20										
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100								
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	94	92	90	89								
2	103	97	91	87	101	95	90	86	91	87	84	88	85	82	85	83	80	78								
3	96	87	81	76	94	86	80	75	83	78	74	81	76	72	78	74	71	69								
4	90	80	72	67	87	78	72	66	76	70	66	74	69	65	72	68	64	62								
5	84	73	65	60	82	72	65	59	70	64	59	68	63	58	66	62	58	56								
6	78	67	59	54	77	66	59	54	64	58	53	63	57	53	61	56	53	51								
7	73	62	54	49	72	61	54	49	60	53	49	58	53	48	57	52	48	46								
8	69	57	50	45	68	57	50	45	55	49	45	54	49	44	53	48	44	42								
9	65	53	46	41	64	53	46	41	52	45	41	51	45	41	50	45	41	39								
10	61	50	43	38	60	49	43	38	48	42	38	48	42	38	47	42	38	36								

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	258619	258619	258619
5°	257997	258257	258257
10°	255006	255269	255006
15°	251946	251946	251946
20°	241600	242165	242453
25°	225975	226275	226860
30°	202489	203101	203101
35°	164385	165710	166026
40°	124079	124755	125126
45°	95033	94667	94667
50°	78292	77889	77889
55°	67202	66750	66750
60°	59971	59428	59428
65°	56358	56358	56358
70°	52437	52437	52437
75°	47609	48610	47609
80°	44750	43187	44750
85°	36796	36796	36796



TEST NUMBER: P580627
 CATALOG NUMBER: HCC4W40D010MW-HM43040927-41WDW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	197.5	6.1
10°-20°	552.8	17.1
20°-30°	759.6	23.5
30°-40°	683.0	21.1
40°-50°	431.6	13.3
50°-60°	281.8	8.7
60°-70°	190.9	5.9
70°-80°	107.5	3.3
80°-90°	30.2	0.9
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1510.0	46.7
0°-40°	2193.1	67.8
0°-60°	2906.4	89.8
0°-90°	3234.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3234.9	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	2097	2097	2097	2097	2097	
5°	2084	2084	2086	2086	2086	197
15°	1973	1973	1973	1973	1973	552
25°	1660	1663	1663	1667	1667	758
35°	1092	1096	1100	1105	1103	680
45°	545	543	543	543	543	432
55°	312	312	310	312	310	283
65°	193	193	193	193	193	191
75°	100	102	102	102	100	107
85°	26	26	26	26	26	30
90°	0	0	0	0	0	



TEST NUMBER: P580627

CATALOG NUMBER: HCC4W40D010MW-HM43040927-41WDW

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	2096.7	2096.7	2096.7	2096.7	2096.7
2.5°	2085.8	2085.8	2085.8	2085.8	2085.8
5°	2083.7	2083.7	2085.8	2085.8	2085.8
7.5°	2068.5	2070.7	2070.7	2070.7	2070.7
10°	2036.0	2036.0	2038.1	2038.1	2036.0
12.5°	2005.6	2005.6	2005.6	2007.7	2005.6
15°	1973.0	1973.0	1973.0	1973.0	1973.0
17.5°	1916.6	1918.7	1918.7	1918.7	1918.7
20°	1840.6	1844.9	1844.9	1847.1	1847.1
22.5°	1753.8	1755.9	1758.1	1760.3	1758.1
25°	1660.4	1662.6	1662.6	1666.9	1666.9
27.5°	1551.9	1554.0	1558.4	1558.4	1558.4
30°	1421.7	1423.9	1426.0	1426.0	1426.0
32.5°	1267.6	1267.6	1271.9	1274.1	1271.9
35°	1091.7	1096.1	1100.5	1104.7	1102.6
37.5°	924.6	929.0	931.1	931.1	933.3
40°	770.6	774.8	774.8	779.2	777.1
42.5°	648.9	646.8	646.8	651.2	648.9
45°	544.8	542.7	542.7	542.7	542.7
47.5°	468.8	466.7	466.7	466.7	466.7
50°	408.0	405.9	405.9	405.9	405.9
52.5°	358.2	355.9	355.9	355.9	353.8
55°	312.5	312.5	310.4	312.5	310.4
57.5°	271.3	271.3	271.3	271.3	271.3
60°	243.1	240.9	240.9	240.9	240.9
62.5°	217.0	217.0	217.0	217.0	217.0
65°	193.1	193.1	193.1	193.1	193.1
67.5°	169.3	167.1	169.3	169.3	167.1
70°	145.4	143.3	145.4	145.4	145.4
72.5°	121.5	121.5	121.5	123.8	121.5
75°	99.9	102.0	102.0	102.0	99.9
77.5°	80.3	82.5	80.3	80.3	80.3
80°	63.0	60.8	60.8	60.8	63.0
82.5°	43.4	43.4	43.4	43.4	43.4
85°	26.0	26.0	26.0	26.0	26.0
87.5°	10.9	10.9	10.9	10.9	10.9
90°	0.0	0.0	0.0	0.0	0.0

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180° - - 45°-225° - - - - 90°-270°

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)