

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P580647

Luminaire Tested: **HCC4W40D010BZ-HM43040930-41RWWH**

Issue Date: 9/9/2021

Test Information

Test Method: LM-41-14
Report Number: P580647
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2106-266-15)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/9/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HCC4W40D010BZ-HM43040930-41RWWH
Description: HALO COMMERCIAL 4" ROUND, NEW CONSTRUCTION FRAME, WITH 4" WALLWASH DISTRIBUTION, HAZE TRIM
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
CYLINDER
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3574.5 lumens
Efficiency: N/A
Efficacy: 87.2 lumens/watt
Spacing Criteria (0/90/45): 1.14 / 1.08 / 1.16
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 41
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P580647
CATALOG NUMBER: HCC4W40D010BZ-HM43040930-41RWWH

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab
 1121 Highway 74 South
 Peachtree City, GA 30269



TEST NUMBER: P580647

CATALOG NUMBER: HCC4W40D010BZ-HM43040930-41RWWH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0					
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100								
1	111	107	104	100	108	105	102	99	101	98	96	97	95	93	93	92	90	88								
2	103	96	90	85	100	94	89	84	90	86	82	87	84	80	84	81	79	77								
3	95	86	79	73	92	84	78	73	81	76	71	79	74	70	76	72	69	67								
4	88	77	70	64	86	76	69	63	74	67	62	71	66	62	69	65	61	59								
5	81	70	62	56	79	69	61	56	67	60	55	65	59	55	63	58	54	52								
6	76	64	56	50	74	63	55	50	61	54	49	60	54	49	58	53	49	47								
7	71	58	51	45	69	58	50	45	56	49	45	55	49	44	54	48	44	42								
8	66	54	46	41	65	53	46	41	52	45	40	51	45	40	50	44	40	38								
9	62	50	42	37	61	49	42	37	48	41	37	47	41	37	46	41	37	35								
10	58	46	39	34	57	46	39	34	45	38	34	44	38	34	43	38	34	32								

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°
0°	231310	231310	231310
5°	237382	231339	227006
10°	242757	229330	220287
15°	249596	226087	214492
20°	248912	217422	205792
25°	238428	203546	195939
30°	219324	187477	185483
35°	192935	170137	171538
40°	166926	152289	158682
45°	145079	135311	143457
50°	128740	119357	127416
55°	114211	104706	109201
60°	101711	90807	90807
65°	90418	75475	70689
70°	78150	57125	50417
75°	65481	37792	31072
80°	49580	18255	16550
85°	26323	6652	6652



TEST NUMBER: P580647
 CATALOG NUMBER: HCC4W40D010BZ-HM43040930-41RWWH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	177.6	5.0
10°-20°	503.5	14.1
20°-30°	710.1	19.9
30°-40°	733.6	20.5
40°-50°	621.8	17.4
50°-60°	452.4	12.7
60°-70°	264.4	7.4
70°-80°	98.2	2.7
80°-90°	12.9	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1391.2	38.9
0°-40°	2124.7	59.4
0°-60°	3199.0	89.5
0°-90°	3574.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3574.5	100.0

CANDELA DISTRIBUTION:

	0°	45°	90°	135°	180°	Flux
0°	1875	1875	1875	1875	1875	
5°	1917	1901	1868	1840	1833	184
15°	1955	1894	1770	1696	1680	549
25°	1752	1654	1496	1442	1440	801
35°	1281	1225	1130	1132	1139	800
45°	832	808	776	804	822	647
55°	531	506	487	503	508	478
65°	310	284	259	242	242	307
75°	137	114	79	63	65	148
85°	19	12	5	5	5	26
90°	0	0	0	0	0	

Cooper Lighting Solutions Photometric Lab
 1121 Highway 74 South
 Peachtree City, GA 30269



TEST NUMBER: P580647

CATALOG NUMBER: HCC4W40D010BZ-HM43040930-41RWWH

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°
0°	1875.3	1875.3	1875.3	1875.3	1875.3	1875.3	1875.3	1875.3	1875.3
2.5°	1891.7	1887.0	1882.4	1875.3	1866.0	1859.1	1852.1	1847.4	1847.4
5°	1917.2	1910.3	1901.0	1884.6	1868.4	1854.4	1840.5	1833.4	1833.4
7.5°	1936.0	1926.7	1907.9	1884.6	1856.7	1835.7	1814.8	1805.5	1800.8
10°	1938.2	1928.9	1903.3	1868.4	1831.0	1798.5	1775.2	1761.2	1758.8
12.5°	1942.9	1931.3	1898.6	1849.8	1800.8	1761.2	1735.5	1721.6	1716.9
15°	1954.6	1938.2	1894.0	1831.0	1770.5	1724.0	1696.0	1684.3	1679.7
17.5°	1942.9	1919.6	1866.0	1791.5	1724.0	1672.6	1644.7	1633.1	1633.1
20°	1896.3	1873.1	1810.1	1728.6	1656.4	1607.4	1579.5	1572.5	1567.8
22.5°	1831.0	1805.5	1737.9	1651.7	1579.5	1535.2	1516.6	1507.3	1504.9
25°	1751.9	1726.2	1654.0	1565.5	1495.6	1458.3	1442.1	1442.1	1439.7
27.5°	1663.3	1630.7	1556.2	1479.3	1411.8	1383.8	1376.8	1376.8	1379.2
30°	1539.9	1516.6	1453.7	1379.2	1316.3	1297.6	1297.6	1302.3	1302.3
32.5°	1407.1	1390.8	1334.9	1269.6	1220.8	1209.1	1213.7	1223.0	1225.4
35°	1281.3	1262.7	1225.4	1167.2	1129.9	1125.3	1132.2	1139.2	1139.2
37.5°	1157.9	1139.2	1113.6	1067.0	1039.1	1041.3	1050.7	1060.0	1067.0
40°	1036.7	1022.7	1004.1	966.8	945.8	955.2	966.8	976.2	985.5
42.5°	929.5	915.5	901.6	873.6	859.6	871.2	885.3	894.6	903.9
45°	831.7	822.4	808.4	785.0	775.7	787.4	803.8	813.1	822.4
47.5°	747.8	743.1	724.5	703.5	698.9	710.5	724.5	736.2	743.1
50°	670.9	664.0	647.6	626.6	622.0	640.7	650.0	656.9	664.0
52.5°	596.4	589.4	570.8	552.1	552.1	566.1	573.1	575.4	582.4
55°	531.1	524.2	505.6	491.6	486.9	498.5	503.2	503.2	507.8
57.5°	470.6	463.6	444.9	428.7	426.3	433.3	433.3	433.3	435.6
60°	412.3	405.4	386.7	372.7	368.1	370.4	368.1	365.8	368.1
62.5°	358.7	351.8	333.2	316.8	312.2	312.2	305.1	302.9	305.1
65°	309.8	298.2	284.2	267.9	258.6	251.6	242.2	242.2	242.2
67.5°	261.0	251.6	235.3	218.9	207.4	195.7	181.7	186.4	188.7
70°	216.7	209.6	191.0	174.8	158.4	144.4	132.8	137.4	139.8
72.5°	177.0	167.7	151.4	132.8	118.8	100.2	93.2	97.9	97.9
75°	137.4	128.1	114.1	95.5	79.3	62.9	62.9	65.2	65.2
77.5°	102.5	93.2	79.3	62.9	48.9	37.3	39.6	39.6	39.6
80°	69.8	62.9	51.2	37.3	25.7	21.0	21.0	21.0	23.3
82.5°	39.6	35.0	27.9	18.6	11.7	11.7	11.7	11.7	11.7
85°	18.6	14.0	11.7	7.0	4.7	4.7	4.7	4.7	4.7
87.5°	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180° - - 45°-225° - - - - 90°-270°

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)