

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P581858

Luminaire Tested: **HCC6W20D010MB-HM60525830-61MDH**

Issue Date: 9/16/2021

**Test Information**

Test Method: LM-41-14  
Report Number: P581858  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2105-241-5)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 9/16/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: HALO COMMERCIAL  
Catalog Number: HCC6W20D010MB-HM60525830-61MDH  
Description: HALO COMMERCIAL 6" ROUND, NEW CONSTRUCTION FRAME, WITH 6" MEDIUM DISTRIBUTION, HAZE TRIM  
Light Source: (1) HIGH LUMEN LED 80CRI / 3000K CCT  
CYLINDER  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 2040.0 lumens  
Efficiency: N/A  
Efficacy: 102.0 lumens/watt  
Spacing Criteria (0/90/45): 1.01 / 1.01 / 0.97  
Luminous Opening: Circular (Dia: 0.5' x H: 0')  
CIE Type: Direct

Input Watts (W): 20  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P581858  
CATALOG NUMBER: HCC6W20D010MB-HM60525830-61MDH

### Luminous Intensity Polar Plot





TEST NUMBER: P581858  
 CATALOG NUMBER: HCC6W20D010MB-HM60525830-61MDH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									20									
RC	80									70									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																			
RCR																																														
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100									100																			
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	94	93									93																			
2	107	102	98	94	105	100	96	93	97	94	91	94	91	89	91	89	87	85									85																			
3	101	94	89	85	99	93	88	84	90	86	83	88	84	81	86	83	80	79									79																			
4	96	88	82	77	94	86	81	77	84	79	76	82	78	75	80	77	74	72									72																			
5	90	81	75	71	89	80	75	70	79	74	70	77	73	69	75	72	68	67									67																			
6	85	76	70	65	84	75	69	65	74	68	64	72	67	64	71	67	63	62									62																			
7	81	71	65	60	79	70	64	60	69	64	60	68	63	59	67	62	59	57									57																			
8	77	67	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53									53																			
9	73	62	56	52	72	62	56	52	61	56	52	60	55	52	59	55	51	50									50																			
10	69	59	53	49	68	58	52	48	57	52	48	57	52	48	56	51	48	47									47																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	102168
5°	102074
10°	101017
15°	98985
20°	93767
25°	84676
30°	71929
35°	53110
40°	30715
45°	16304
50°	9211
55°	4817
60°	3158
65°	2244
70°	1619
75°	1228
80°	884
85°	943



TEST NUMBER: P581858  
 CATALOG NUMBER: HCC6W20D010MB-HM60525830-61MDH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	175.8	8.6
10°-20°	487.8	23.9
20°-30°	636.7	31.2
30°-40°	486.6	23.9
40°-50°	176.2	8.6
50°-60°	51.2	2.5
60°-70°	18.3	0.9
70°-80°	6.3	0.3
80°-90°	1.2	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1300.3	63.7
0°-40°	1786.9	87.6
0°-60°	2014.2	98.7
0°-90°	2040.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2040.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1864	
5°	1855	176
15°	1744	488
25°	1400	637
35°	794	487
45°	210	176
55°	50	51
65°	17	18
75°	6	6
85°	2	1
90°	0	



TEST NUMBER: P581858  
CATALOG NUMBER: HCC6W20D010MB-HM60525830-61MDH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1863.7
2.5°	1854.9
5°	1854.9
7.5°	1842.0
10°	1814.7
12.5°	1783.0
15°	1744.1
17.5°	1686.5
20°	1607.3
22.5°	1509.4
25°	1399.9
27.5°	1276.0
30°	1136.3
32.5°	979.4
35°	793.6
37.5°	599.1
40°	429.2
42.5°	296.7
45°	210.3
47.5°	151.3
50°	108.0
52.5°	76.4
55°	50.4
57.5°	36.0
60°	28.8
62.5°	23.0
65°	17.3
67.5°	14.4
70°	10.1
72.5°	7.3
75°	5.8
77.5°	4.3
80°	2.8
82.5°	1.5
85°	1.5
87.5°	0.0
90°	0.0

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)