

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P582235

Luminaire Tested: **HCC6S30D010MB-HM63040935-61MDC**

Issue Date: 9/16/2021

**Test Information**

Test Method: LM-41-14  
Report Number: P582235  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2105-241-4)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 9/16/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: HALO COMMERCIAL  
Catalog Number: HCC6S30D010MB-HM63040935-61MDC  
Description: HALO COMMERCIAL 6" ROUND, NEW CONSTRUCTION FRAME, WITH 6" MEDIUM DISTRIBUTION, SPECULAR TRIM  
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT  
CYLINDER  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 3210.4 lumens  
Efficiency: N/A  
Efficacy: 114.7 lumens/watt  
Spacing Criteria (0/90/45): 1.06 / 1.06 / 0.96  
Luminous Opening: Circular (Dia: 0.5' x H: 0')  
CIE Type: Direct

Input Watts (W): 28  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P582235  
CATALOG NUMBER: HCC6S30D010MB-HM63040935-61MDC

### Luminous Intensity Polar Plot





TEST NUMBER: P582235  
 CATALOG NUMBER: HCC6S30D010MB-HM63040935-61MDC

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20		
RC	80				70				50				30				10		0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10		0
RCR																			
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102		100
1	114	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95		94
2	108	103	99	96	106	101	98	95	98	95	93	95	93	91	92	90	89		87
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82		81
4	97	90	84	80	95	89	83	80	86	82	79	84	81	78	83	79	77		75
5	92	84	78	74	91	83	78	73	81	76	73	80	75	72	78	74	72		70
6	88	79	73	68	86	78	72	68	76	71	68	75	71	67	74	70	67		65
7	83	74	68	64	82	73	68	63	72	67	63	71	66	63	70	66	62		61
8	79	70	63	59	78	69	63	59	68	63	59	67	62	59	66	62	58		57
9	75	66	60	56	74	65	59	55	64	59	55	63	58	55	62	58	55		54
10	72	62	56	52	71	61	56	52	61	55	52	60	55	52	59	55	52		50

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	152460
5°	154831
10°	163646
15°	182209
20°	188964
25°	155035
30°	108637
35°	74124
40°	38615
45°	13575
50°	6072
55°	1940
60°	1118
65°	791
70°	641
75°	424
80°	0
85°	0



TEST NUMBER: P582235  
 CATALOG NUMBER: HCC6S30D010MB-HM63040935-61MDC

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	272.5	8.5
10°-20°	902.9	28.1
20°-30°	1149.7	35.8
30°-40°	685.2	21.3
40°-50°	166.2	5.2
50°-60°	25.5	0.8
60°-70°	6.2	0.2
70°-80°	2.1	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2325.2	72.4
0°-40°	3010.4	93.8
0°-60°	3202.1	99.7
0°-90°	3210.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3210.4	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	2781	
5°	2814	273
15°	3210	903
25°	2563	1150
35°	1108	685
45°	175	166
55°	20	25
65°	6	6
75°	2	2
85°	0	0
90°	0	



TEST NUMBER: P582235  
CATALOG NUMBER: HCC6S30D010MB-HM63040935-61MDC

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	2781.1
2.5°	2781.1
5°	2813.6
7.5°	2864.5
10°	2939.8
12.5°	3057.9
15°	3210.5
17.5°	3306.3
20°	3239.1
22.5°	2980.6
25°	2563.1
27.5°	2103.1
30°	1716.2
32.5°	1402.8
35°	1107.6
37.5°	816.4
40°	539.6
42.5°	291.2
45°	175.1
47.5°	110.0
50°	71.2
52.5°	42.8
55°	20.3
57.5°	12.2
60°	10.2
62.5°	8.1
65°	6.1
67.5°	4.0
70°	4.0
72.5°	2.0
75°	2.0
77.5°	2.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)