

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P584443

Luminaire Tested: **HCC8W35D010MB-HM82555927-81NDH**

Issue Date: 10/21/2021

**Test Information**

Test Method: LM-41-14  
Report Number: P584443  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2109-368-2)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 10/21/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: HALO COMMERCIAL  
Catalog Number: HCC8W35D010MB-HM82555927-81NDH  
Description: HALO COMMERCIAL 8" ROUND, NEW CONSTRUCTION FRAME, WITH 8" NARROW DISTRIBUTION, HAZE TRIM  
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT CYLINDER  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 2915.0 lumens  
Efficiency: N/A  
Efficacy: 86.5 lumens/watt  
Spacing Criteria (0/90/45): 0.42 / 0.42 / 0.57  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct

Input Watts (W): 33.7  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P584443  
CATALOG NUMBER: HCC8W35D010MB-HM82555927-81NDH

### Luminous Intensity Polar Plot





TEST NUMBER: P584443

CATALOG NUMBER: HCC8W35D010MB-HM82555927-81NDH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	114	112	109	107	112	109	107	106	105	104	102	102	100	99	98	97	96	95			95
2	109	105	101	98	107	103	100	97	100	97	95	97	95	93	94	92	91	89			89
3	104	99	94	91	102	97	93	90	95	91	88	92	90	87	90	88	86	84			84
4	100	93	88	84	98	92	87	84	90	86	83	88	85	82	86	83	81	80			80
5	96	88	83	79	94	87	82	79	86	81	78	84	80	77	82	79	77	75			75
6	92	84	78	75	90	83	78	74	81	77	74	80	76	73	79	76	73	72			72
7	88	80	74	70	87	79	74	70	78	73	70	77	73	70	76	72	69	68			68
8	84	76	71	67	83	75	70	67	74	70	66	73	69	66	72	69	66	65			65
9	81	72	67	64	80	72	67	63	71	66	63	70	66	63	69	66	63	62			62
10	78	69	64	61	77	69	64	61	68	63	60	67	63	60	67	63	60	59			59

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	231948
5°	196506
10°	142576
15°	107070
20°	84480
25°	68143
30°	50497
35°	20456
40°	8626
45°	4627
50°	2072
55°	1048
60°	666
65°	474
70°	388
75°	262
80°	391
85°	778



TEST NUMBER: P584443  
 CATALOG NUMBER: HCC8W35D010MB-HM82555927-81NDH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	545.1	18.7
10°-20°	942.0	32.3
20°-30°	910.8	31.2
30°-40°	400.0	13.7
40°-50°	86.4	3.0
50°-60°	19.4	0.7
60°-70°	6.6	0.2
70°-80°	2.6	0.1
80°-90°	2.1	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2397.8	82.3
0°-40°	2797.8	96.0
0°-60°	2903.7	99.6
0°-90°	2915.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2915.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	7522	
5°	6348	545
15°	3354	942
25°	2003	911
35°	543	400
45°	106	86
55°	20	19
65°	6	7
75°	2	3
85°	2	2
90°	0	



TEST NUMBER: P584443  
CATALOG NUMBER: HCC8W35D010MB-HM82555927-81NDH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	7521.9
1°	7465.6
2°	7311.9
3°	7034.7
4°	6703.4
5°	6348.3
6°	5960.8
7°	5571.1
8°	5205.1
9°	4865.2
10°	4553.4
11°	4258.9
12°	3994.7
13°	3754.4
14°	3542.2
15°	3353.9
17.5°	2931.6
20°	2574.4
22.5°	2260.5
25°	2002.8
27.5°	1740.8
30°	1418.2
32.5°	963.6
35°	543.4
37.5°	320.5
40°	214.3
42.5°	151.5
45°	106.1
47.5°	69.2
50°	43.2
52.5°	26.0
55°	19.5
57.5°	15.2
60°	10.8
62.5°	8.6
65°	6.5
67.5°	4.3
70°	4.3
72.5°	2.2
75°	2.2
77.5°	2.2
80°	2.2
82.5°	2.2

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



TEST NUMBER: P584443  
CATALOG NUMBER: HCC8W35D010MB-HM82555927-81NDH

**CANDELA DISTRIBUTION (continued):**

0°  
90° | 0.0

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



85°	2.2
87.5°	2.2

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)