

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P584595

Luminaire Tested: **HCC8S40D010MW-HM82555930-81NDC**

Issue Date: 10/21/2021

**Test Information**

Test Method: LM-41-14  
Report Number: P584595  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2109-368-1)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 10/21/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: HALO COMMERCIAL  
Catalog Number: HCC8S40D010MW-HM82555930-81NDC  
Description: HALO COMMERCIAL 8" ROUND, NEW CONSTRUCTION FRAME, WITH 8" NARROW DISTRIBUTION, SPECULAR TRIM  
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT  
CYLINDER  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 4411.0 lumens  
Efficiency: N/A  
Efficacy: 107.6 lumens/watt  
Spacing Criteria (0/90/45): 0.22 / 0.22 / 0.27  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct

Input Watts (W): 41  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P584595  
CATALOG NUMBER: HCC8S40D010MW-HM82555930-81NDC

### Luminous Intensity Polar Plot





TEST NUMBER: P584595  
 CATALOG NUMBER: HCC8S40D010MW-HM82555930-81NDC

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20					20					20					20					20																		
RC	80					70					50					30					10					0													
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0									
RCR																																							
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100									100												
1	115	112	110	108	112	110	108	106	106	105	103	102	101	100	99	98	97	96	96	94	93	91									96								
2	110	106	103	100	108	104	101	99	101	99	97	98	96	95	96	94	93	91	91	89	87	87									91								
3	106	101	97	93	104	99	96	93	97	94	91	95	92	90	92	90	89	87	87	85	83	83									87								
4	102	96	91	88	100	95	91	88	93	89	87	91	88	86	89	87	85	83	83	81	81	80									83								
5	98	92	87	83	97	91	86	83	89	85	82	87	84	82	86	83	81	80	80	77	75	75									80								
6	95	88	83	79	93	87	82	79	86	82	79	84	81	78	83	80	78	76	76	74	72	72									76								
7	91	84	79	76	90	83	79	76	82	78	75	81	78	75	80	77	75	73	73	71	71	70									73								
8	88	81	76	73	87	80	76	73	79	75	72	78	75	72	77	74	72	70	70	68	68	67									71								
9	85	78	73	70	84	77	73	70	76	72	70	76	72	69	75	72	69	67	67	65	65	64									68								
10	83	75	70	67	82	75	70	67	74	70	67	73	69	67	73	69	67	65	65	63	63	62									66								

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	830231
5°	532525
10°	240564
15°	145146
20°	110611
25°	89323
30°	65456
35°	23701
40°	8848
45°	4016
50°	1286
55°	317
60°	185
65°	219
70°	0
75°	0
80°	533
85°	1061



TEST NUMBER: P584595  
 CATALOG NUMBER: HCC8S40D010MW-HM82555930-81NDC

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	1312.1	29.7
10°-20°	1332.7	30.2
20°-30°	1193.0	27.0
30°-40°	480.6	10.9
40°-50°	78.8	1.8
50°-60°	7.2	0.2
60°-70°	2.6	0.1
70°-80°	2.0	0.0
80°-90°	2.9	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3837.8	87.0
0°-40°	4318.4	97.9
0°-60°	4404.4	99.8
0°-90°	4411.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4411.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	26924	
5°	17204	###
15°	4547	1333
25°	2625	1193
35°	630	481
45°	92	79
55°	6	7
65°	3	3
75°	0	2
85°	3	3
90°	0	



TEST NUMBER: P584595  
CATALOG NUMBER: HCC8S40D010MW-HM82555930-81NDC

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	26923.8
0.5°	26840.6
1°	26493.1
1.5°	25934.9
2°	25088.4
2.5°	24087.6
3°	22834.4
3.5°	21459.4
4°	20099.2
4.5°	18575.8
5°	17203.7
5.5°	15710.0
6°	14498.4
6.5°	13236.1
7°	12244.3
7.5°	11196.0
8°	10352.5
8.5°	9506.2
9°	8870.6
9.5°	8169.8
10°	7682.8
12.5°	5666.3
15°	4546.6
17.5°	3884.4
20°	3370.7
22.5°	2960.8
25°	2625.3
27.5°	2289.7
30°	1838.3
32.5°	1181.9
35°	629.6
37.5°	347.5
40°	219.8
42.5°	145.5
45°	92.1
47.5°	56.4
50°	26.8
52.5°	8.9
55°	5.9
57.5°	3.0
60°	3.0
62.5°	3.0
65°	3.0



TEST NUMBER: P584595  
CATALOG NUMBER: HCC8S40D010MW-HM82555930-81NDC

**CANDELA DISTRIBUTION (continued):**

	0°
72.5°	0.0
75°	0.0
77.5°	3.0
80°	3.0
82.5°	3.0
85°	3.0
87.5°	3.0
90°	0.0

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



67.5°		3.0
70°		0.0

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)