

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P584823

Luminaire Tested: **HCC8S50D010MW-HM82555835-81WDC**

Issue Date: 10/21/2021

Test Information

Test Method: LM-41-14
 Report Number: P584823
 TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2109-368-7)
 Test Lab: COOPER LIGHTING SOLUTIONS
 Issue Date: 10/21/2021
 Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
 Product Line: HALO COMMERCIAL
 Catalog Number: HCC8S50D010MW-HM82555835-81WDC
 Description: HALO COMMERCIAL 8" ROUND, NEW CONSTRUCTION FRAME, WITH 8" WIDE DISTRIBUTION, SPECULAR TRIM
 Light Source: (1) HIGH LUMEN LED 80CRI / 3500K CCT
 CYLINDER
 Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
 Luminaire Lumens: 6032.2 lumens
 Efficiency: N/A
 Efficacy: 125.7 lumens/watt
 Spacing Criteria (0/90/45): 1.1 / 1.1 / 1.05
 Luminous Opening: Circular (Dia: 0.67' x H: 0')
 CIE Type: Direct

Input Watts (W): 48
 Input Voltage (V): NR
 Input Current (A_{in}): NR
 Voltage Rise (V): NR
 Power Factor: NR
 Total Harmonic Distortion (THDi): NR
 Frequency (hertz): 60
 Stabilization Time: NR
 Operation Time: NR
 Ambient Temperature (°C): NR
 Test Distance: 25 FT



TEST NUMBER: P584823
CATALOG NUMBER: HCC8S50D010MW-HM82555835-81WDC

Luminous Intensity Polar Plot





TEST NUMBER: P584823

CATALOG NUMBER: HCC8S50D010MW-HM82555835-81WDC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100	
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	96	95	94	92			92	
2	106	101	96	93	104	99	95	92	96	92	90	93	90	88	90	88	86	84			84	
3	100	93	87	83	98	91	86	82	89	84	81	86	83	79	84	81	78	77			77	
4	94	86	79	75	92	84	79	74	82	77	73	80	76	72	78	75	71	70			70	
5	88	79	72	68	87	78	72	67	76	71	67	74	70	66	73	69	65	64			64	
6	83	73	66	62	82	72	66	61	71	65	61	69	64	61	68	64	60	59			59	
7	78	68	61	57	77	67	61	56	66	60	56	65	60	56	63	59	55	54			54	
8	74	63	57	52	73	63	56	52	62	56	52	60	55	51	59	55	51	50			50	
9	70	59	53	48	69	59	52	48	58	52	48	57	51	48	56	51	47	46			46	
10	66	55	49	45	65	55	49	45	54	48	44	53	48	44	52	48	44	43			43	

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	144727
5°	140832
10°	139764
15°	137679
20°	133512
25°	128529
30°	120062
35°	99358
40°	59986
45°	40400
50°	29110
55°	16602
60°	7308
65°	2619
70°	974
75°	429
80°	0
85°	0



TEST NUMBER: P584823
 CATALOG NUMBER: HCC8S50D010MW-HM82555835-81WDC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	432.2	7.2
10°-20°	1212.0	20.1
20°-30°	1729.0	28.7
30°-40°	1574.4	26.1
40°-50°	742.7	12.3
50°-60°	292.0	4.8
60°-70°	46.5	0.8
70°-80°	3.3	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3373.2	55.9
0°-40°	4947.7	82.0
0°-60°	5982.4	99.2
0°-90°	6032.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6032.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4693	
5°	4550	432
15°	4313	1212
25°	3778	1729
35°	2639	1574
45°	926	743
55°	309	292
65°	36	47
75°	4	3
85°	0	0
90°	0	



TEST NUMBER: P584823
CATALOG NUMBER: HCC8S50D010MW-HM82555835-81WDC

CANDELA DISTRIBUTION (FULL):

	0°
0°	4693.4
2.5°	4632.3
5°	4549.7
7.5°	4503.1
10°	4463.6
12.5°	4398.9
15°	4312.7
17.5°	4205.0
20°	4068.6
22.5°	3924.9
25°	3777.6
27.5°	3598.2
30°	3371.9
32.5°	3066.6
35°	2639.4
37.5°	2039.7
40°	1490.2
42.5°	1145.5
45°	926.4
47.5°	761.3
50°	606.8
52.5°	456.0
55°	308.8
57.5°	193.9
60°	118.5
62.5°	71.8
65°	35.9
67.5°	18.0
70°	10.8
72.5°	3.6
75°	3.6
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)