

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P584925

Luminaire Tested: **HCC8W55D010MW-HM82555827-81WDC**

Issue Date: 10/21/2021

**Test Information**

Test Method: LM-41-14  
Report Number: P584925  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2109-368-7)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 10/21/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: HALO COMMERCIAL  
Catalog Number: HCC8W55D010MW-HM82555827-81WDC  
Description: HALO COMMERCIAL 8" ROUND, NEW CONSTRUCTION FRAME, WITH 8" WIDE DISTRIBUTION, SPECULAR TRIM  
Light Source: (1) HIGH LUMEN LED 80CRI / 2700K CCT CYLINDER  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 6100.1 lumens  
Efficiency: N/A  
Efficacy: 117.3 lumens/watt  
Spacing Criteria (0/90/45): 1.1 / 1.1 / 1.05  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct

Input Watts (W): 52  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P584925  
CATALOG NUMBER: HCC8W55D010MW-HM82555827-81WDC

### Luminous Intensity Polar Plot





TEST NUMBER: P584925  
 CATALOG NUMBER: HCC8W55D010MW-HM82555827-81WDC

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20					20					20					20					20										
RC	80					70					50					30					10					0					
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0				
RCR																															
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100													
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	96	95	94	92													
2	106	101	96	93	104	99	95	92	96	92	90	93	90	88	90	88	86	84													
3	100	93	87	83	98	91	86	82	89	84	81	86	83	79	84	81	78	77													
4	94	86	79	75	92	84	79	74	82	77	73	80	76	72	78	75	71	70													
5	88	79	72	68	87	78	72	67	76	71	67	74	70	66	73	69	65	64													
6	83	73	66	62	82	72	66	61	71	65	61	69	64	61	68	64	60	59													
7	78	68	61	57	77	67	61	56	66	60	56	65	60	56	63	59	55	54													
8	74	63	57	52	73	63	56	52	62	56	52	60	55	51	59	55	51	50													
9	70	59	53	48	69	59	52	48	58	52	48	57	51	48	56	51	47	46													
10	66	55	49	45	65	55	49	45	54	48	44	53	48	44	52	48	44	43													

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	146352
5°	142417
10°	141333
15°	139227
20°	135012
25°	129975
30°	121412
35°	100472
40°	60663
45°	40857
50°	29441
55°	16790
60°	7388
65°	2649
70°	983
75°	429
80°	0
85°	0



TEST NUMBER: P584925  
 CATALOG NUMBER: HCC8W55D010MW-HM82555827-81WDC

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	437.1	7.2
10°-20°	1225.7	20.1
20°-30°	1748.4	28.7
30°-40°	1592.1	26.1
40°-50°	751.1	12.3
50°-60°	295.4	4.8
60°-70°	47.1	0.8
70°-80°	3.3	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3411.2	55.9
0°-40°	5003.3	82.0
0°-60°	6049.7	99.2
0°-90°	6100.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6100.1	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	4746	
5°	4601	437
15°	4361	1226
25°	3820	1748
35°	2669	1592
45°	937	751
55°	312	295
65°	36	47
75°	4	3
85°	0	0
90°	0	



TEST NUMBER: P584925  
CATALOG NUMBER: HCC8W55D010MW-HM82555827-81WDC

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	4746.1
2.5°	4684.4
5°	4600.9
7.5°	4553.7
10°	4513.7
12.5°	4448.4
15°	4361.2
17.5°	4252.3
20°	4114.3
22.5°	3969.1
25°	3820.1
27.5°	3638.6
30°	3409.8
32.5°	3101.1
35°	2669.0
37.5°	2062.6
40°	1507.0
42.5°	1158.4
45°	936.9
47.5°	769.9
50°	613.7
52.5°	461.2
55°	312.3
57.5°	196.1
60°	119.8
62.5°	72.7
65°	36.3
67.5°	18.2
70°	10.9
72.5°	3.6
75°	3.6
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)