

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P584962

Luminaire Tested: **HCC8W55D010MB-HM82555835-81WDWB**

Issue Date: 10/21/2021

**Test Information**

Test Method: LM-41-14  
Report Number: P584962  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2109-368-10)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 10/21/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: HALO COMMERCIAL  
Catalog Number: HCC8W55D010MB-HM82555835-81WDWB  
Description: HALO COMMERCIAL 8" ROUND, NEW CONSTRUCTION FRAME, WITH 8" WIDE DISTRIBUTION, WHITE BAFFLE TRIM  
Light Source: (1) HIGH LUMEN LED 80CRI / 3500K CCT  
CYLINDER  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 6190.3 lumens  
Efficiency: N/A  
Efficacy: 119.0 lumens/watt  
Spacing Criteria (0/90/45): 1.32 / 1.32 / 1.14  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct

Input Watts (W): 52  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P584962  
CATALOG NUMBER: HCC8W55D010MB-HM82555835-81WDWB

### Luminous Intensity Polar Plot





TEST NUMBER: P584962  
 CATALOG NUMBER: HCC8W55D010MB-HM82555835-81WDWB

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100	
1	112	108	105	103	109	106	103	101	102	100	98	98	97	95	95	93	92	90			90	
2	105	99	94	89	102	97	92	88	93	90	86	90	87	84	88	85	83	81			81	
3	98	90	84	79	96	88	83	78	86	81	77	83	79	76	81	77	74	73			73	
4	92	82	75	70	90	81	75	70	79	73	69	77	72	68	75	71	67	65			65	
5	86	75	68	63	84	74	68	63	73	67	62	71	66	62	69	65	61	59			59	
6	80	69	62	57	79	69	62	57	67	61	56	65	60	56	64	59	56	54			54	
7	75	64	57	52	74	63	57	52	62	56	51	61	55	51	59	55	51	49			49	
8	71	59	52	47	69	59	52	47	58	51	47	56	51	47	55	50	47	45			45	
9	67	55	48	43	65	55	48	43	54	47	43	53	47	43	52	47	43	41			41	
10	63	51	45	40	62	51	44	40	50	44	40	49	44	40	48	43	40	38			38	

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	108717
5°	107968
10°	107685
15°	110512
20°	119641
25°	128271
30°	125403
35°	104421
40°	64153
45°	44420
50°	33898
55°	22230
60°	13907
65°	10427
70°	10504
75°	12093
80°	13336
85°	11994



TEST NUMBER: P584962  
 CATALOG NUMBER: HCC8W55D010MB-HM82555835-81WDWB

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	331.4	5.4
10°-20°	993.7	16.1
20°-30°	1710.7	27.6
30°-40°	1657.4	26.8
40°-50°	816.4	13.2
50°-60°	385.2	6.2
60°-70°	151.8	2.5
70°-80°	104.7	1.7
80°-90°	38.9	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3035.9	49.0
0°-40°	4693.3	75.8
0°-60°	5894.9	95.2
0°-90°	6190.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6190.3	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3526	
5°	3488	331
15°	3462	994
25°	3770	1711
35°	2774	1657
45°	1019	816
55°	414	385
65°	143	152
75°	102	105
85°	34	39
90°	0	



TEST NUMBER: P584962  
CATALOG NUMBER: HCC8W55D010MB-HM82555835-81WDWB

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	3525.6
2.5°	3514.4
5°	3488.0
7.5°	3461.7
10°	3439.1
12.5°	3435.4
15°	3461.7
17.5°	3540.6
20°	3645.9
22.5°	3739.9
25°	3770.0
27.5°	3702.2
30°	3521.9
32.5°	3224.9
35°	2773.9
37.5°	2153.7
40°	1593.7
42.5°	1236.6
45°	1018.6
47.5°	857.0
50°	706.6
52.5°	556.2
55°	413.5
57.5°	300.7
60°	225.5
62.5°	176.6
65°	142.9
67.5°	124.0
70°	116.5
72.5°	109.0
75°	101.5
77.5°	90.2
80°	75.1
82.5°	56.4
85°	33.9
87.5°	15.0
90°	0.0

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)