

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P585029

Luminaire Tested: **HCC8S55D010MW-HM82555935-81WDW**

Issue Date: 10/21/2021

Test Information

Test Method: LM-41-14
Report Number: P585029
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2109-368-9)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 10/21/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HCC8S55D010MW-HM82555935-81WDW
Description: HALO COMMERCIAL 8" ROUND, NEW CONSTRUCTION FRAME, WITH 8" WIDE DISTRIBUTION, WHITE TRIM
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
CYLINDER
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5383.7 lumens
Efficiency: N/A
Efficacy: 103.5 lumens/watt
Spacing Criteria (0/90/45): 1.17 / 1.17 / 1.06
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct

Input Watts (W): 52
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P585029
CATALOG NUMBER: HCC8S55D010MW-HM82555935-81WDW

Luminous Intensity Polar Plot





TEST NUMBER: P585029

CATALOG NUMBER: HCC8S55D010MW-HM82555935-81WDW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	111	108	104	101	109	105	102	100	101	99	96	97	95	94	94	92	91	89				89
2	104	97	92	87	101	95	90	86	92	88	84	89	85	82	86	83	81	79				79
3	97	88	82	76	94	87	81	76	84	79	75	81	77	73	79	75	72	70				70
4	90	80	73	68	88	79	73	67	77	71	67	75	70	66	73	68	65	63				63
5	84	74	66	61	82	73	66	61	71	65	60	69	64	59	67	63	59	57				57
6	79	68	61	55	77	67	60	55	65	59	55	64	58	54	62	58	54	52				52
7	74	63	56	50	73	62	55	50	61	54	50	59	54	50	58	53	49	48				48
8	70	58	51	46	69	58	51	46	57	50	46	55	50	46	54	49	45	44				44
9	66	54	47	43	65	54	47	42	53	47	42	52	46	42	51	46	42	40				40
10	62	51	44	39	61	50	44	39	49	43	39	49	43	39	48	43	39	37				37

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	107634
5°	107504
10°	106442
15°	105168
20°	104192
25°	103022
30°	97203
35°	79154
40°	43732
45°	29188
50°	25891
55°	24300
60°	23991
65°	23779
70°	21485
75°	19194
80°	16799
85°	14895



TEST NUMBER: P585029
 CATALOG NUMBER: HCC8S55D010MW-HM82555935-81WDW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	329.2	6.1
10°-20°	930.2	17.3
20°-30°	1382.1	25.7
30°-40°	1244.6	23.1
40°-50°	551.8	10.2
50°-60°	408.6	7.6
60°-70°	317.8	5.9
70°-80°	172.2	3.2
80°-90°	47.2	0.9
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2641.4	49.1
0°-40°	3886.1	72.2
0°-60°	4846.4	90.0
0°-90°	5383.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5383.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3490	
5°	3473	329
15°	3294	930
25°	3028	1382
35°	2103	1245
45°	669	552
55°	452	409
65°	326	318
75°	161	172
85°	42	47
90°	0	



TEST NUMBER: P585029
CATALOG NUMBER: HCC8S55D010MW-HM82555935-81WDW

CANDELA DISTRIBUTION (FULL):

0°	
0°	3490.5
2.5°	3483.4
5°	3473.0
7.5°	3444.9
10°	3399.4
12.5°	3346.8
15°	3294.3
17.5°	3241.6
20°	3175.1
22.5°	3108.5
25°	3027.9
27.5°	2905.2
30°	2729.9
32.5°	2477.6
35°	2102.7
37.5°	1570.0
40°	1086.4
42.5°	802.5
45°	669.3
47.5°	592.2
50°	539.7
52.5°	490.6
55°	452.0
57.5°	420.5
60°	389.0
62.5°	361.0
65°	325.9
67.5°	283.9
70°	238.3
72.5°	199.7
75°	161.1
77.5°	126.1
80°	94.6
82.5°	66.6
85°	42.1
87.5°	17.6
90°	0.0

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)