

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P585141

Luminaire Tested: **HCC8W60D010BZ-HM86080930-81NDW**

Issue Date: 10/21/2021

**Test Information**

Test Method: LM-41-14  
Report Number: P585141  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2109-368-3)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 10/21/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: HALO COMMERCIAL  
Catalog Number: HCC8W60D010BZ-HM86080930-81NDW  
Description: HALO COMMERCIAL 8" ROUND, NEW CONSTRUCTION FRAME, WITH 8" NARROW DISTRIBUTION, WHITE TRIM  
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT  
CYLINDER  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 4350.0 lumens  
Efficiency: N/A  
Efficacy: 77.7 lumens/watt  
Spacing Criteria (0/90/45): 1.06 / 1.06 / 0.92  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct

Input Watts (W): 56  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P585141  
CATALOG NUMBER: HCC8W60D010BZ-HM86080930-81NDW

### Luminous Intensity Polar Plot





TEST NUMBER: P585141

CATALOG NUMBER: HCC8W60D010BZ-HM86080930-81NDW

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	112	108	105	102	109	106	103	101	102	100	98	98	96	95	95	93	92	90			
2	105	99	94	90	102	97	92	88	94	90	87	91	87	85	88	85	83	81			
3	98	90	84	79	96	89	83	79	86	81	77	84	80	76	81	78	75	73			
4	92	83	76	71	90	82	76	71	80	74	70	77	73	69	75	72	68	67			
5	87	77	70	65	85	76	69	64	74	68	64	72	67	63	70	66	63	61			
6	82	71	64	59	80	70	64	59	69	63	58	67	62	58	66	61	58	56			
7	77	66	59	54	76	66	59	54	64	58	54	63	58	54	62	57	53	52			
8	73	62	55	50	71	61	55	50	60	54	50	59	54	50	58	53	49	48			
9	69	58	51	47	68	57	51	47	56	51	46	55	50	46	55	50	46	45			
10	65	55	48	44	64	54	48	44	53	47	43	52	47	43	52	47	43	42			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	108430
5°	108135
10°	106336
15°	104781
20°	102269
25°	97081
30°	80072
35°	41228
40°	27602
45°	23667
50°	20422
55°	17822
60°	15831
65°	14228
70°	12893
75°	11616
80°	10388
85°	10367



TEST NUMBER: P585141  
 CATALOG NUMBER: HCC8W60D010BZ-HM86080930-81NDW

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	330.3	7.6
10°-20°	923.5	21.2
20°-30°	1279.5	29.4
30°-40°	768.5	17.7
40°-50°	420.7	9.7
50°-60°	298.9	6.9
60°-70°	194.0	4.5
70°-80°	103.7	2.4
80°-90°	31.0	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2533.2	58.2
0°-40°	3301.8	75.9
0°-60°	4021.4	92.4
0°-90°	4350.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4350.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3516	
5°	3493	330
15°	3282	923
25°	2853	1279
35°	1095	769
45°	543	421
55°	332	299
65°	195	194
75°	98	104
85°	29	31
90°	0	



TEST NUMBER: P585141  
CATALOG NUMBER: HCC8W60D010BZ-HM86080930-81NDW

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	3516.3
2.5°	3509.7
5°	3493.4
7.5°	3454.4
10°	3396.0
12.5°	3340.7
15°	3282.2
17.5°	3207.5
20°	3116.5
22.5°	3006.0
25°	2853.3
27.5°	2612.8
30°	2248.8
32.5°	1647.6
35°	1095.2
37.5°	809.2
40°	685.7
42.5°	607.7
45°	542.7
47.5°	481.0
50°	425.7
52.5°	373.7
55°	331.5
57.5°	292.5
60°	256.7
62.5°	224.2
65°	195.0
67.5°	165.7
70°	143.0
72.5°	117.0
75°	97.5
77.5°	78.0
80°	58.5
82.5°	42.2
85°	29.3
87.5°	13.0
90°	0.0

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)