

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P585189

Luminaire Tested: **HCC8W80D010BZ-HM86080827-81MDW**

Issue Date: 10/21/2021

Test Information

Test Method: LM-41-14
Report Number: P585189
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2109-368-6)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 10/21/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HCC8W80D010BZ-HM86080827-81MDW
Description: HALO COMMERCIAL 8" ROUND, NEW CONSTRUCTION FRAME, WITH 8" MEDIUM DISTRIBUTION, WHITE TRIM
Light Source: (1) HIGH LUMEN LED 80CRI / 2700K CCT
CYLINDER
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 6168.0 lumens
Efficiency: N/A
Efficacy: 88.1 lumens/watt
Spacing Criteria (0/90/45): 1 / 1 / 0.95
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct

Input Watts (W): 70
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P585189
CATALOG NUMBER: HCC8W80D010BZ-HM86080827-81MDW

Luminous Intensity Polar Plot





TEST NUMBER: P585189

CATALOG NUMBER: HCC8W80D010BZ-HM86080827-81MDW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	92	90	90	90	90
2	104	98	93	89	102	96	92	88	93	89	86	90	87	84	87	84	82	80	80	80	80
3	98	89	83	78	95	88	82	78	85	80	76	83	78	75	80	77	74	72	72	72	72
4	91	82	75	70	89	81	74	69	78	73	69	76	72	68	74	70	67	65	65	65	65
5	86	76	68	63	84	75	68	63	73	67	62	71	66	62	69	65	61	59	59	59	59
6	81	70	63	58	79	69	62	57	67	61	57	66	61	56	64	60	56	54	54	54	54
7	76	65	58	53	74	64	57	53	63	57	52	62	56	52	60	55	52	50	50	50	50
8	72	61	54	49	70	60	53	49	59	53	48	58	52	48	57	52	48	46	46	46	46
9	68	57	50	45	67	56	50	45	55	49	45	54	49	45	53	48	45	43	43	43	43
10	64	53	46	42	63	53	46	42	52	46	42	51	46	42	50	45	42	40	40	40	40

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	157712
5°	153415
10°	144367
15°	136686
20°	131481
25°	126403
30°	112264
35°	71494
40°	39904
45°	33418
50°	30170
55°	28440
60°	25946
65°	23400
70°	20656
75°	18360
80°	16284
85°	14718



TEST NUMBER: P585189
 CATALOG NUMBER: HCC8W80D010BZ-HM86080827-81MDW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	462.1	7.5
10°-20°	1207.5	19.6
20°-30°	1684.5	27.3
30°-40°	1212.1	19.7
40°-50°	600.7	9.7
50°-60°	470.0	7.6
60°-70°	318.2	5.2
70°-80°	165.2	2.7
80°-90°	47.6	0.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3354.1	54.4
0°-40°	4566.2	74.0
0°-60°	5636.9	91.4
0°-90°	6168.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6168.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5114	
5°	4956	462
15°	4282	1208
25°	3715	1685
35°	1899	1212
45°	766	601
55°	529	470
65°	321	318
75°	154	165
85°	42	48
90°	0	



TEST NUMBER: P585189
CATALOG NUMBER: HCC8W80D010BZ-HM86080827-81MDW

CANDELA DISTRIBUTION (FULL):

	0°
0°	5114.5
2.5°	5068.7
5°	4956.2
7.5°	4798.0
10°	4610.6
12.5°	4435.7
15°	4281.6
17.5°	4135.8
20°	4006.7
22.5°	3877.6
25°	3715.1
27.5°	3481.9
30°	3152.9
32.5°	2636.4
35°	1899.2
37.5°	1295.3
40°	991.3
42.5°	853.8
45°	766.3
47.5°	691.4
50°	628.9
52.5°	574.8
55°	529.0
57.5°	474.8
60°	420.7
62.5°	366.6
65°	320.7
67.5°	274.9
70°	229.1
72.5°	191.5
75°	154.1
77.5°	120.8
80°	91.7
82.5°	66.6
85°	41.6
87.5°	20.8
90°	0.0

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)