

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P303334

Luminaire Tested: **PR6FS24D010 PR6M24MD9FSMMS 2000Lm4000K**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P303334
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1903-195-2)
Test Lab: INNOVATION CENTER(G3)
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: PR6FS24D010 PR6M24MD9FSMMS 2000Lm4000K
Description: PR6 MEDIUM LENS WITH, MATTE METALLIC SILVER FINISH
Light Source: ARRAY OF HIGH LUMEN LEDs 90CRI / 4000K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1894.4 lumens
Efficiency: N/A
Efficacy: 86.1 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.25
Luminous Opening: Circular (Dia: 0.46' x H: 0')
CIE Type: Direct


Input Watts (W): 22
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P303334

CATALOG NUMBER: PR6FS24D010 PR6M24MD9FSMMS 2000Lm4000K

Luminous Intensity Polar Plot





TEST NUMBER: P303334

CATALOG NUMBER: PR6FS24D010 PR6M24MD9FSMMS 2000Lm4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	91	89
2	104	97	92	87	101	95	90	86	92	88	84	89	85	82	86	83	81	79
3	96	87	81	75	94	86	80	75	83	78	74	80	76	72	78	74	71	69
4	89	79	72	66	87	78	71	66	75	69	65	73	68	64	71	67	63	61
5	83	72	64	58	81	71	63	58	69	62	57	67	61	57	65	60	56	54
6	77	65	58	52	75	64	57	52	63	56	51	61	55	51	60	55	51	49
7	72	60	52	47	70	59	52	46	58	51	46	56	50	46	55	50	46	44
8	67	55	47	42	66	54	47	42	53	47	42	52	46	42	51	45	41	40
9	63	51	43	38	62	50	43	38	49	43	38	48	42	38	47	42	38	36
10	59	47	40	35	58	47	40	35	46	39	35	45	39	35	44	39	35	33

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	63525
5°	63512
10°	63206
15°	62720
20°	62027
25°	60921
30°	59476
35°	56484
40°	52224
45°	45366
50°	36589
55°	27628
60°	19429
65°	12998
70°	8221
75°	4941
80°	2931
85°	1497



TEST NUMBER: P303334

CATALOG NUMBER: PR6FS24D010 PR6M24MD9FSMMS 2000Lm4000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	92.0	4.9
10°-20°	261.9	13.8
20°-30°	389.5	20.6
30°-40°	441.8	23.3
40°-50°	376.0	19.8
50°-60°	220.1	11.6
60°-70°	87.3	4.6
70°-80°	23.2	1.2
80°-90°	2.7	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	743.4	39.2
0°-40°	1185.2	62.6
0°-60°	1781.3	94.0
0°-90°	1894.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1894.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	974	
5°	970	92
15°	929	262
25°	846	390
35°	709	442
45°	492	376
55°	243	220
65°	84	87
75°	20	23
85°	2	3
90°	0	



TEST NUMBER: P303334

CATALOG NUMBER: PR6FS24D010 PR6M24MD9FSMMS 2000Lm4000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	973.7
2.5°	971.7
5°	969.8
7.5°	961.9
10°	954.1
12.5°	942.3
15°	928.6
17.5°	913.0
20°	893.4
22.5°	871.8
25°	846.3
27.5°	818.9
30°	789.5
32.5°	752.3
35°	709.2
37.5°	664.1
40°	613.2
42.5°	554.4
45°	491.7
47.5°	423.2
50°	360.5
52.5°	299.7
55°	242.9
57.5°	192.0
60°	148.9
62.5°	113.6
65°	84.2
67.5°	60.7
70°	43.1
72.5°	31.3
75°	19.6
77.5°	11.8
80°	7.8
82.5°	3.9
85°	2.0
87.5°	0.0
90°	0.0

(END OF REPORT)