

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P210139

Luminaire Tested: **PR815D010 - PR8M12MDMMS - 3000K**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P210139  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29044)  
Test Lab: INNOVATION CENTER-P2  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: HALO COMMERCIAL  
Catalog Number: PR815D010 - PR8M12MDMMS - 3000K  
Description: HALO 8" ROUND DOWNLIGHT, MEDIUM LENS, MATTE METALLIC SILVER FINISH  
Light Source: (1) HIGH LUMEN LED 80CRI / 3000K CCT  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1543.5 lumens  
Efficiency: N/A  
Efficacy: 102.9 lumens/watt  
Spacing Criteria (0/90/45): 1.03 / 1.03 / 1.13  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct


Input Watts (W): 15  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P210139

CATALOG NUMBER: PR815D010 - PR8M12MDMMS - 3000K

### Luminous Intensity Polar Plot





TEST NUMBER: P210139

CATALOG NUMBER: PR815D010 - PR8M12MDMMS - 3000K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |     | 20  |     |     |     | 20  |     |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |     | 30  |     |     |     | 10  | 0   |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 0   |
| RCR |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 |
| 1   | 111 | 107 | 104 | 101 | 109 | 105 | 102 | 99  | 101 | 99  | 96  | 97  | 95  | 93  | 94  | 92  | 91  | 89  |
| 2   | 103 | 96  | 91  | 86  | 100 | 94  | 89  | 85  | 91  | 87  | 83  | 88  | 84  | 81  | 85  | 82  | 79  | 77  |
| 3   | 95  | 86  | 79  | 74  | 93  | 85  | 78  | 73  | 82  | 76  | 72  | 79  | 75  | 71  | 77  | 73  | 70  | 68  |
| 4   | 88  | 78  | 70  | 64  | 86  | 76  | 69  | 64  | 74  | 68  | 63  | 72  | 67  | 62  | 70  | 65  | 61  | 60  |
| 5   | 82  | 70  | 62  | 57  | 80  | 69  | 62  | 56  | 67  | 61  | 56  | 65  | 60  | 55  | 64  | 59  | 55  | 53  |
| 6   | 76  | 64  | 56  | 50  | 74  | 63  | 56  | 50  | 61  | 55  | 50  | 60  | 54  | 49  | 58  | 53  | 49  | 47  |
| 7   | 71  | 59  | 51  | 45  | 69  | 58  | 50  | 45  | 56  | 50  | 45  | 55  | 49  | 44  | 54  | 48  | 44  | 42  |
| 8   | 66  | 54  | 46  | 41  | 65  | 53  | 46  | 41  | 52  | 45  | 41  | 51  | 45  | 40  | 50  | 44  | 40  | 38  |
| 9   | 62  | 50  | 42  | 37  | 61  | 49  | 42  | 37  | 48  | 42  | 37  | 47  | 41  | 37  | 46  | 41  | 37  | 35  |
| 10  | 59  | 46  | 39  | 34  | 57  | 46  | 39  | 34  | 45  | 38  | 34  | 44  | 38  | 34  | 43  | 38  | 34  | 32  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |       |
|-----|-------|
|     | 0°    |
| 0°  | 26606 |
| 5°  | 26515 |
| 10° | 25823 |
| 15° | 24760 |
| 20° | 23358 |
| 25° | 22122 |
| 30° | 20438 |
| 35° | 18664 |
| 40° | 17422 |
| 45° | 15913 |
| 50° | 15049 |
| 55° | 13553 |
| 60° | 10589 |
| 65° | 7377  |
| 70° | 4679  |
| 75° | 2645  |
| 80° | 746   |
| 85° | 0     |



TEST NUMBER: P210139

CATALOG NUMBER: PR815D010 - PR8M12MDMMS - 3000K

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 80.8   | 5.2       |
| 10°-20°   | 217.3  | 14.1      |
| 20°-30°   | 297.5  | 19.3      |
| 30°-40°   | 311.9  | 20.2      |
| 40°-50°   | 284.3  | 18.4      |
| 50°-60°   | 221.9  | 14.4      |
| 60°-70°   | 103.3  | 6.7       |
| 70°-80°   | 25.7   | 1.7       |
| 80°-90°   | 0.8    | 0.0       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 595.6  | 38.6      |
| 0°-40°    | 907.5  | 58.8      |
| 0°-60°    | 1413.7 | 91.6      |
| 0°-90°    | 1543.5 | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 1543.5 | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 863 |      |
| 5°  | 857 | 81   |
| 15° | 776 | 217  |
| 25° | 650 | 298  |
| 35° | 496 | 312  |
| 45° | 365 | 284  |
| 55° | 252 | 222  |
| 65° | 101 | 103  |
| 75° | 22  | 26   |
| 85° | 0   | 1    |
| 90° | 0   |      |



TEST NUMBER: P210139

CATALOG NUMBER: PR815D010 - PR8M12MDMMS - 3000K

**CANDELA DISTRIBUTION (FULL):**

|       | 0°    |
|-------|-------|
| 0°    | 862.8 |
| 2.5°  | 858.6 |
| 5°    | 856.6 |
| 7.5°  | 846.2 |
| 10°   | 824.7 |
| 12.5° | 799.8 |
| 15°   | 775.6 |
| 17.5° | 745.1 |
| 20°   | 711.8 |
| 22.5° | 680.7 |
| 25°   | 650.2 |
| 27.5° | 613.5 |
| 30°   | 574.0 |
| 32.5° | 533.9 |
| 35°   | 495.8 |
| 37.5° | 463.9 |
| 40°   | 432.8 |
| 42.5° | 399.5 |
| 45°   | 364.9 |
| 47.5° | 337.2 |
| 50°   | 313.7 |
| 52.5° | 287.4 |
| 55°   | 252.1 |
| 57.5° | 212.6 |
| 60°   | 171.7 |
| 62.5° | 133.0 |
| 65°   | 101.1 |
| 67.5° | 73.4  |
| 70°   | 51.9  |
| 72.5° | 35.3  |
| 75°   | 22.2  |
| 77.5° | 12.5  |
| 80°   | 4.2   |
| 82.5° | 0.7   |
| 85°   | 0.0   |
| 87.5° | 0.0   |
| 90°   | 0.0   |

(END OF REPORT)