

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P210288

Luminaire Tested: **PR815D010 - PR8M12WDMW - 3500K**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P210288
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29051)
Test Lab: INNOVATION CENTER-P2
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: PR815D010 - PR8M12WDMW - 3500K
Description: HALO 8" ROUND DOWNLIGHT, WIDE LENS, MATTE WHITE FINISH
Light Source: (1) HIGH LUMEN LED 80CRI / 3500K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1794.1 lumens
Efficiency: N/A
Efficacy: 119.6 lumens/watt
Spacing Criteria (0/90/45): 1.37 / 1.37 / 1.39
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 15
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P210288

CATALOG NUMBER: PR815D010 - PR8M12WDMW - 3500K

Luminous Intensity Polar Plot





TEST NUMBER: P210288

CATALOG NUMBER: PR815D010 - PR8M12WDMW - 3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	110	106	103	99	108	104	101	98	100	97	95		96	94	92		92	91	89	87
2	102	94	88	83	99	92	87	82	89	84	80		86	82	79		83	80	77	75
3	93	84	77	71	91	82	76	70	79	74	69		77	72	68		74	70	67	65
4	86	75	67	61	84	74	66	61	71	65	60		69	64	59		67	62	58	56
5	80	68	59	53	78	67	59	53	64	58	52		63	57	52		61	56	51	49
6	74	61	53	47	72	60	52	47	59	52	46		57	51	46		55	50	46	44
7	68	56	48	42	67	55	47	42	53	46	41		52	46	41		51	45	41	39
8	64	51	43	37	62	50	43	37	49	42	37		48	42	37		47	41	37	35
9	60	47	39	34	58	46	39	34	45	38	34		44	38	33		43	37	33	31
10	56	43	36	31	55	43	36	31	42	35	31		41	35	30		40	34	30	29

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	21767
5°	22132
10°	22401
15°	22816
20°	23296
25°	23507
30°	23472
35°	23415
40°	22599
45°	20697
50°	17289
55°	14376
60°	12082
65°	9982
70°	8583
75°	6732
80°	4670
85°	4918



TEST NUMBER: P210288

CATALOG NUMBER: PR815D010 - PR8M12WDMW - 3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	68.1	3.8
10°-20°	202.2	11.3
20°-30°	317.6	17.7
30°-40°	387.1	21.6
40°-50°	361.8	20.2
50°-60°	241.3	13.5
60°-70°	138.8	7.7
70°-80°	64.0	3.6
80°-90°	13.0	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	587.9	32.8
0°-40°	975.0	54.3
0°-60°	1578.2	88.0
0°-90°	1794.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1794.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	706	
5°	715	68
15°	715	202
25°	691	318
35°	622	387
45°	475	362
55°	267	241
65°	137	139
75°	56	64
85°	14	13
90°	0	



TEST NUMBER: P210288

CATALOG NUMBER: PR815D010 - PR8M12WDMW - 3500K

CANDELA DISTRIBUTION (FULL):

	0°
0°	705.9
2.5°	707.0
5°	715.0
7.5°	714.3
10°	715.4
12.5°	713.9
15°	714.7
17.5°	713.2
20°	709.9
22.5°	698.2
25°	690.9
27.5°	676.4
30°	659.2
32.5°	642.1
35°	622.0
37.5°	597.9
40°	561.4
42.5°	521.7
45°	474.6
47.5°	422.4
50°	360.4
52.5°	307.9
55°	267.4
57.5°	228.7
60°	195.9
62.5°	167.4
65°	136.8
67.5°	112.4
70°	95.2
72.5°	81.0
75°	56.5
77.5°	44.9
80°	26.3
82.5°	16.8
85°	13.9
87.5°	4.0
90°	0.0

(END OF REPORT)