

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P210286

Luminaire Tested: **PR820D010 - PR8M12MDMMS - 3500K**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P210286
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29044)
Test Lab: INNOVATION CENTER-P2
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: PR820D010 - PR8M12MDMMS - 3500K
Description: HALO 8" ROUND DOWNLIGHT, MEDIUM LENS, MATTE METALLIC SILVER FINISH
Light Source: (1) HIGH LUMEN LED 80CRI / 3500K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2382.2 lumens
Efficiency: N/A
Efficacy: 108.3 lumens/watt
Spacing Criteria (0/90/45): 1.03 / 1.03 / 1.13
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 22
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P210286

CATALOG NUMBER: PR820D010 - PR8M12MDMMS - 3500K

Luminous Intensity Polar Plot





TEST NUMBER: P210286

CATALOG NUMBER: PR820D010 - PR8M12MDMMS - 3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	111	107	104	101	109	105	102	99	101	99	96		97	95	93		94	92	91	89
2	103	96	91	86	100	94	89	85	91	87	83		88	84	81		85	82	79	77
3	95	86	79	74	93	85	78	73	82	76	72		79	75	71		77	73	70	68
4	88	78	70	64	86	76	69	64	74	68	63		72	67	62		70	65	61	60
5	82	70	62	57	80	69	62	56	67	61	56		65	60	55		64	59	55	53
6	76	64	56	50	74	63	56	50	61	55	50		60	54	49		58	53	49	47
7	71	59	51	45	69	58	50	45	56	50	45		55	49	44		54	48	44	42
8	66	54	46	41	65	53	46	41	52	45	41		51	45	40		50	44	40	38
9	62	50	42	37	61	49	42	37	48	42	37		47	41	37		46	41	37	35
10	59	46	39	34	57	46	39	34	45	38	34		44	38	34		43	38	34	32

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	41065
5°	40924
10°	39857
15°	38213
20°	36054
25°	34147
30°	31548
35°	28805
40°	26890
45°	24561
50°	23224
55°	20913
60°	16349
65°	11383
70°	7231
75°	4075
80°	1137
85°	0



TEST NUMBER: P210286

CATALOG NUMBER: PR820D010 - PR8M12MDMMS - 3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	124.7	5.2
10°-20°	335.4	14.1
20°-30°	459.3	19.3
30°-40°	481.4	20.2
40°-50°	438.8	18.4
50°-60°	342.4	14.4
60°-70°	159.4	6.7
70°-80°	39.7	1.7
80°-90°	1.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	919.3	38.6
0°-40°	1400.7	58.8
0°-60°	2181.9	91.6
0°-90°	2382.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2382.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1332	
5°	1322	125
15°	1197	335
25°	1004	459
35°	765	481
45°	563	439
55°	389	342
65°	156	159
75°	34	40
85°	0	1
90°	0	



TEST NUMBER: P210286

CATALOG NUMBER: PR820D010 - PR8M12MDMMS - 3500K

CANDELA DISTRIBUTION (FULL):

	0°
0°	1331.7
2.5°	1325.3
5°	1322.1
7.5°	1306.0
10°	1272.9
12.5°	1234.4
15°	1197.0
17.5°	1150.0
20°	1098.7
22.5°	1050.6
25°	1003.6
27.5°	946.9
30°	886.0
32.5°	824.0
35°	765.2
37.5°	716.1
40°	668.0
42.5°	616.7
45°	563.2
47.5°	520.5
50°	484.1
52.5°	443.5
55°	389.0
57.5°	328.1
60°	265.1
62.5°	205.2
65°	156.0
67.5°	113.3
70°	80.2
72.5°	54.5
75°	34.2
77.5°	19.2
80°	6.4
82.5°	1.1
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)