

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P210569

Luminaire Tested: **PR8S15D010 - PR8M12WDMB - 3000K**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P210569  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29051)  
Test Lab: INNOVATION CENTER-P2  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: HALO COMMERCIAL  
Catalog Number: PR8S15D010 - PR8M12WDMB - 3000K  
Description: HALO 8" ROUND DOWNLIGHT, WIDE LENS, MATTE BLACK FINISH  
Light Source: (1) HIGH LUMEN LED 80CRI / 3000K CCT  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1220.2 lumens  
Efficiency: N/A  
Efficacy: 81.3 lumens/watt  
Spacing Criteria (0/90/45): 1.37 / 1.37 / 1.39  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct


Input Watts (W): 15  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P210569

CATALOG NUMBER: PR8S15D010 - PR8M12WDMB - 3000K

### Luminous Intensity Polar Plot





TEST NUMBER: P210569

CATALOG NUMBER: PR8S15D010 - PR8M12WDMB - 3000K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	110	106	103	99	108	104	101	98	100	97	95	96	94	92	92	91	89	87
2	102	94	88	83	99	92	87	82	89	84	80	86	82	79	83	80	77	75
3	93	84	77	71	91	82	76	70	79	74	69	77	72	68	74	70	67	65
4	86	75	67	61	84	74	66	61	71	65	60	69	64	59	67	62	58	56
5	80	68	59	53	78	67	59	53	64	58	52	63	57	52	61	56	51	49
6	74	61	53	47	72	60	52	47	59	52	46	57	51	46	55	50	46	44
7	68	56	48	42	67	55	47	42	53	46	41	52	46	41	51	45	41	39
8	64	51	43	37	62	50	43	37	49	42	37	48	42	37	47	41	37	35
9	60	47	39	34	58	46	39	34	45	38	34	44	38	33	43	37	33	31
10	56	43	36	31	55	43	36	31	42	35	31	41	35	30	40	34	30	29

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	14805
5°	15053
10°	15233
15°	15518
20°	15843
25°	15988
30°	15962
35°	15923
40°	15369
45°	14077
50°	11758
55°	9779
60°	8215
65°	6786
70°	5842
75°	4587
80°	3179
85°	3326



TEST NUMBER: P210569

CATALOG NUMBER: PR8S15D010 - PR8M12WDMB - 3000K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	46.3	3.8
10°-20°	137.5	11.3
20°-30°	216.0	17.7
30°-40°	263.3	21.6
40°-50°	246.1	20.2
50°-60°	164.1	13.5
60°-70°	94.4	7.7
70°-80°	43.6	3.6
80°-90°	8.8	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	399.9	32.8
0°-40°	663.1	54.3
0°-60°	1073.4	88.0
0°-90°	1220.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1220.2	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	480	
5°	486	46
15°	486	138
25°	470	216
35°	423	263
45°	323	246
55°	182	164
65°	93	94
75°	38	44
85°	9	9
90°	0	



TEST NUMBER: P210569

CATALOG NUMBER: PR8S15D010 - PR8M12WDMB - 3000K

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	480.1
2.5°	480.8
5°	486.3
7.5°	485.8
10°	486.5
12.5°	485.6
15°	486.1
17.5°	485.1
20°	482.8
22.5°	474.9
25°	469.9
27.5°	460.0
30°	448.3
32.5°	436.7
35°	423.0
37.5°	406.7
40°	381.8
42.5°	354.8
45°	322.8
47.5°	287.3
50°	245.1
52.5°	209.4
55°	181.9
57.5°	155.6
60°	133.2
62.5°	113.9
65°	93.0
67.5°	76.4
70°	64.8
72.5°	55.1
75°	38.5
77.5°	30.5
80°	17.9
82.5°	11.4
85°	9.4
87.5°	2.7
90°	0.0

(END OF REPORT)