

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P885695

Luminaire Tested: ML104LSFL95FS1E-TIR1D40FL-TL1RDMWB-340LM-3500K

Issue Date: 6/19/2024

Test Information

Test Method: LM-79-2019
Report Number: P885695
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2402-314-127)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 6/19/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML104LSFL95FS1E-TIR1D40FL-TL1RDMWB-340LM-3500K
Description: 1IN ROUND ML FLEX, SELECTABLE CCT, WITH 40D TIR, MATTE WHITE BAFFLED TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 95CRI / 3500K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 405.7 lumens
Efficiency: N/A
Efficacy: 66.5 lumens/watt
Spacing Criteria (0/90/45): 0.67 / 0.67 / 0.66
Luminous Opening: Circular (Dia: 0.08' x H: 0')
CIE Type: Direct

Input Watts (W): 6.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P885695
CATALOG NUMBER: ML104LSFL95FS1E-TIR1D40FL-TL1RDMWB-340LM-3500K

Luminous Intensity Polar Plot





TEST NUMBER: P885695

CATALOG NUMBER: ML104LSFL95FS1E-TIR1D40FL-TL1RDMWB-340LM-3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	109	106	111	109	107	105	105	103	102	101	100	99	98	97	96	94			
2	109	104	100	97	106	102	99	96	99	96	94	96	94	92	93	91	90	88			
3	104	98	93	89	102	96	92	88	94	90	87	91	88	86	89	87	84	83			
4	99	92	87	83	97	91	86	82	89	85	82	87	83	81	85	82	80	78			
5	95	87	82	78	93	86	81	77	84	80	77	83	79	76	81	78	75	74			
6	91	83	77	73	89	82	77	73	80	76	72	79	75	72	78	74	71	70			
7	87	78	73	69	86	78	73	69	77	72	69	75	71	68	74	71	68	67			
8	83	75	69	66	82	74	69	65	73	68	65	72	68	65	71	67	65	63			
9	80	71	66	62	79	71	66	62	70	65	62	69	65	62	68	64	62	60			
10	77	68	63	59	76	68	63	59	67	62	59	66	62	59	66	62	59	58			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1470683
5°	1441038
10°	1322832
15°	1110049
20°	814877
25°	549617
30°	317900
35°	157324
40°	89139
45°	41307
50°	30396
55°	27182
60°	23288
65°	22882
70°	23081
75°	22876
80°	22730
85°	22644

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 41307 cd/sqm



TEST NUMBER: P885695

CATALOG NUMBER: ML104LSFL95FS1E-TIR1D40FL-TL1RDMWB-340LM-3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	67.3	16.6
10°-20°	148.1	36.5
20°-30°	115.5	28.5
30°-40°	45.2	11.1
40°-50°	13.4	3.3
50°-60°	6.8	1.7
60°-70°	5.1	1.3
70°-80°	3.4	0.8
80°-90°	0.8	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	330.8	81.5
0°-40°	376.1	92.7
0°-60°	396.3	97.7
0°-90°	405.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	405.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	745	
5°	727	67
15°	543	148
25°	252	115
35°	65	45
45°	15	13
55°	8	7
65°	5	5
75°	3	3
85°	1	1
90°	0	



TEST NUMBER: P885695

CATALOG NUMBER: ML104LSFL95FS1E-TIR1D40FL-TL1RDMWB-340LM-3500K

CANDELA DISTRIBUTION (FULL):

	0°
0°	745.2
2.5°	743.3
5°	727.4
7.5°	699.7
10°	660.1
12.5°	608.7
15°	543.3
17.5°	469.1
20°	388.0
22.5°	315.7
25°	252.4
27.5°	195.0
30°	139.5
32.5°	95.0
35°	65.3
37.5°	48.5
40°	34.6
42.5°	22.8
45°	14.8
47.5°	10.9
50°	9.9
52.5°	7.9
55°	7.9
57.5°	6.9
60°	5.9
62.5°	5.9
65°	4.9
67.5°	4.9
70°	4.0
72.5°	4.0
75°	3.0
77.5°	3.0
80°	2.0
82.5°	1.0
85°	1.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)