

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P885702

Luminaire Tested: ML104LSFL95FS1E-TIR1D40FL-TL1RDSL-340LM-5000K

Issue Date: 6/19/2024

Test Information

Test Method: LM-79-2019
Report Number: P885702
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2402-314-125)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 6/19/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML104LSFL95FS1E-TIR1D40FL-TL1RDSL-340LM-5000K
Description: 1IN ROUND ML FLEX, SELECTABLE CCT, WITH 40D TIR, METALLIC SILVER TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 95CRI / 5000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 498.7 lumens
Efficiency: N/A
Efficacy: 81.8 lumens/watt
Spacing Criteria (0/90/45): 0.65 / 0.65 / 0.66
Luminous Opening: Circular (Dia: 0.08' x H: 0')
CIE Type: Direct

Input Watts (W): 6.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P885702
CATALOG NUMBER: ML104LSFL95FS1E-TIR1D40FL-TL1RDSL-340LM-5000K

Luminous Intensity Polar Plot





TEST NUMBER: P885702

CATALOG NUMBER: ML104LSFL95FS1E-TIR1D40FL-TL1RDSL-340LM-5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	114	111	109	107	112	109	107	105	105	104	102	102	100	99	98	97	96	95																			
2	109	105	101	98	107	103	100	97	100	97	95	97	95	93	94	92	91	89																			
3	104	99	94	91	102	97	93	90	95	91	88	92	89	87	90	88	86	84																			
4	100	93	88	84	98	92	87	84	90	86	83	88	85	82	86	83	81	80																			
5	96	88	83	79	94	87	82	79	86	81	78	84	80	78	83	79	77	76																			
6	92	84	78	75	90	83	78	74	82	77	74	80	76	73	79	76	73	72																			
7	88	80	74	71	87	79	74	70	78	73	70	77	73	70	76	72	69	68																			
8	84	76	71	67	83	75	70	67	74	70	67	73	69	66	73	69	66	65																			
9	81	73	67	64	80	72	67	64	71	67	64	70	66	63	70	66	63	62																			
10	78	69	64	61	77	69	64	61	68	64	61	68	63	61	67	63	60	59																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1893021
5°	1851518
10°	1687758
15°	1386285
20°	1017127
25°	695296
30°	389228
35°	202859
40°	114644
45°	48843
50°	28861
55°	19956
60°	13815
65°	10741
70°	6924
75°	9150
80°	13638
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 48843 cd/sqm



TEST NUMBER: P885702

CATALOG NUMBER: ML104LSFL95FS1E-TIR1D40FL-TL1RDSL-340LM-5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	86.2	17.3
10°-20°	185.5	37.2
20°-30°	144.5	29.0
30°-40°	57.3	11.5
40°-50°	16.2	3.2
50°-60°	5.3	1.1
60°-70°	2.3	0.5
70°-80°	1.3	0.3
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	416.2	83.4
0°-40°	473.5	94.9
0°-60°	495.0	99.3
0°-90°	498.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	498.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	959	
5°	935	86
15°	678	185
25°	319	145
35°	84	57
45°	18	16
55°	6	5
65°	2	2
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P885702

CATALOG NUMBER: ML104LSFL95FS1E-TIR1D40FL-TL1RDSL-340LM-5000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	959.2
2.5°	956.9
5°	934.6
7.5°	894.9
10°	842.2
12.5°	769.7
15°	678.5
17.5°	580.2
20°	484.3
22.5°	396.5
25°	319.3
27.5°	242.1
30°	170.8
32.5°	119.3
35°	84.2
37.5°	63.2
40°	44.5
42.5°	28.1
45°	17.5
47.5°	12.9
50°	9.4
52.5°	7.0
55°	5.8
57.5°	4.7
60°	3.5
62.5°	2.3
65°	2.3
67.5°	2.3
70°	1.2
72.5°	1.2
75°	1.2
77.5°	1.2
80°	1.2
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)