

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P885752

Luminaire Tested: ML104LSFL95FS1E-TIR1D55WFL-TL1RDMW-340LM-5000K

Issue Date: 6/19/2024

Test Information

Test Method: LM-79-2019
Report Number: P885752
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2402-314-130)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 6/19/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML104LSFL95FS1E-TIR1D55WFL-TL1RDMW-340LM-5000K
Description: 1IN ROUND ML FLEX, SELECTABLE CCT, WITH 55D TIR, MATTE WHITE TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 95CRI / 5000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 457.1 lumens
Efficiency: N/A
Efficacy: 74.9 lumens/watt
Spacing Criteria (0/90/45): 0.81 / 0.81 / 0.77
Luminous Opening: Circular (Dia: 0.08' x H: 0')
CIE Type: Direct

Input Watts (W): 6.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P885752
CATALOG NUMBER: ML104LSFL95FS1E-TIR1D55WFL-TL1RDMW-340LM-5000K

Luminous Intensity Polar Plot





TEST NUMBER: P885752
 CATALOG NUMBER: ML104LSFL95FS1E-TIR1D55WFL-TL1RDMW-340LM-5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	111	108	106	111	108	106	104	104	102	101	101	99	98	97	96	95	93			
2	108	103	99	95	106	101	97	94	98	95	92	95	92	90	92	90	88	87			
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82	81			
4	98	90	85	80	96	89	84	80	87	82	79	85	81	78	83	80	77	76			
5	93	85	79	75	91	84	78	74	82	77	74	80	76	73	79	75	72	71			
6	88	80	74	70	87	79	74	70	78	73	69	76	72	69	75	71	68	67			
7	84	75	70	65	83	75	69	65	73	69	65	72	68	65	71	67	64	63			
8	81	71	66	62	79	71	65	61	70	65	61	69	64	61	68	64	61	59			
9	77	68	62	58	76	67	62	58	66	61	58	65	61	58	65	60	57	56			
10	74	64	59	55	73	64	59	55	63	58	55	62	58	55	62	58	55	53			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1256751
5°	1238373
10°	1172934
15°	1052432
20°	904766
25°	729048
30°	448250
35°	242611
40°	129587
45°	65310
50°	39607
55°	32343
60°	27630
65°	32689
70°	34044
75°	35838
80°	26140
85°	27173

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 65310 cd/sqm



TEST NUMBER: P885752

CATALOG NUMBER: ML104LSFL95FS1E-TIR1D55WFL-TL1RDMW-340LM-5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	58.4	12.8
10°-20°	142.8	31.2
20°-30°	148.0	32.4
30°-40°	66.9	14.6
40°-50°	20.2	4.4
50°-60°	8.5	1.9
60°-70°	6.5	1.4
70°-80°	4.5	1.0
80°-90°	1.3	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	349.2	76.4
0°-40°	416.1	91.0
0°-60°	444.8	97.3
0°-90°	457.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	457.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	637	
5°	625	58
15°	515	143
25°	335	148
35°	101	67
45°	23	20
55°	9	8
65°	7	7
75°	5	4
85°	1	1
90°	0	



TEST NUMBER: P885752

CATALOG NUMBER: ML104LSFL95FS1E-TIR1D55WFL-TL1RDMW-340LM-5000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	636.8
2.5°	635.7
5°	625.1
7.5°	607.6
10°	585.3
12.5°	552.5
15°	515.1
17.5°	471.8
20°	430.8
22.5°	389.8
25°	334.8
27.5°	268.1
30°	196.7
32.5°	140.5
35°	100.7
37.5°	72.6
40°	50.3
42.5°	35.1
45°	23.4
47.5°	16.4
50°	12.9
52.5°	10.5
55°	9.4
57.5°	8.2
60°	7.0
62.5°	7.0
65°	7.0
67.5°	5.9
70°	5.9
72.5°	4.7
75°	4.7
77.5°	3.5
80°	2.3
82.5°	2.3
85°	1.2
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)