

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P886015

Luminaire Tested: ML104LSFLD2W1E-TIR1D40FL-TL1RDMBB-200LM-4000K

Issue Date: 6/19/2024

Test Information

Test Method: LM-79-2019
Report Number: P886015
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2402-314-129)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 6/19/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML104LSFLD2W1E-TIR1D40FL-TL1RDMBB-200LM-4000K
Description: 1IN ROUND ML FLEX, SELECTABLE CCT, WITH 40D TIR, MATTE BLACK BAFFLED TRIM
Light Source: (1) D2W LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 225.2 lumens
Efficiency: N/A
Efficacy: 70.4 lumens/watt
Spacing Criteria (0/90/45): 0.67 / 0.67 / 0.66
Luminous Opening: Circular (Dia: 0.08' x H: 0')
CIE Type: Direct

Input Watts (W): 3.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P886015
CATALOG NUMBER: ML104LSFLD2W1E-TIR1D40FL-TL1RDMBB-200LM-4000K

Luminous Intensity Polar Plot





TEST NUMBER: P886015

CATALOG NUMBER: ML104LSFLD2W1E-TIR1D40FL-TL1RDMBB-200LM-4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95	95	95	95
2	110	105	102	99	107	104	100	98	100	98	96	97	95	94	95	93	92	90	90	90	90
3	105	99	95	92	103	98	94	91	95	92	89	93	90	88	91	89	87	85	85	85	85
4	101	94	89	86	99	93	89	85	91	87	84	89	86	83	87	85	82	81	81	81	81
5	96	89	84	81	95	88	84	80	87	83	80	85	82	79	84	81	78	77	77	77	77
6	93	85	80	76	91	84	79	76	83	78	75	81	78	75	80	77	74	73	73	73	73
7	89	81	76	72	88	80	75	72	79	75	72	78	74	71	77	73	71	70	70	70	70
8	85	77	72	69	84	77	72	68	76	71	68	75	71	68	74	70	68	66	66	66	66
9	82	74	69	65	81	73	68	65	72	68	65	72	68	65	71	67	65	63	63	63	63
10	79	71	66	62	78	70	65	62	69	65	62	69	65	62	68	64	62	61	61	61	61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	854544
5°	838988
10°	773739
15°	650542
20°	480316
25°	323368
30°	186866
35°	85769
40°	44312
45°	14792
50°	5527
55°	2064
60°	0
65°	0
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 14792 cd/sqm



TEST NUMBER: P886015

CATALOG NUMBER: ML104LSFLD2W1E-TIR1D40FL-TL1RDMBB-200LM-4000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	39.2	17.4
10°-20°	86.8	38.6
20°-30°	68.2	30.3
30°-40°	25.1	11.2
40°-50°	5.2	2.3
50°-60°	0.6	0.3
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	194.2	86.3
0°-40°	219.4	97.4
0°-60°	225.2	100.0
0°-90°	225.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	225.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	433	
5°	424	39
15°	318	87
25°	148	68
35°	36	25
45°	5	5
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P886015
CATALOG NUMBER: ML104LSFLD2W1E-TIR1D40FL-TL1RDMBB-200LM-4000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	433.0
2.5°	433.0
5°	423.5
7.5°	408.1
10°	386.1
12.5°	357.0
15°	318.4
17.5°	275.0
20°	228.7
22.5°	187.1
25°	148.5
27.5°	115.2
30°	82.0
32.5°	54.1
35°	35.6
37.5°	25.5
40°	17.2
42.5°	10.1
45°	5.3
47.5°	3.0
50°	1.8
52.5°	1.2
55°	0.6
57.5°	0.0
60°	0.0
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)