

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P886038

Luminaire Tested: ML104LSFLD2W1E-TIR1D55WFL-TL1RDMBB-200LM-3500K

Issue Date: 6/19/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P886038  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2402-314-135)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 6/19/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: HALO  
Catalog Number: ML104LSFLD2W1E-TIR1D55WFL-TL1RDMBB-200LM-3500K  
Description: 1IN ROUND ML FLEX, SELECTABLE CCT, WITH 55D TIR, MATTE BLACK BAFFLED TRIM  
Light Source: (1) D2W LED 90CRI / 2700K CCT  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 202.4 lumens  
Efficiency: N/A  
Efficacy: 63.3 lumens/watt  
Spacing Criteria (0/90/45): 0.81 / 0.81 / 0.78  
Luminous Opening: Circular (Dia: 0.08' x H: 0')  
CIE Type: Direct

Input Watts (W): 3.2  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



TEST NUMBER: P886038  
CATALOG NUMBER: ML104LSFLD2W1E-TIR1D55WFL-TL1RDMMB-200LM-3500K

### Luminous Intensity Polar Plot





TEST NUMBER: P886038

CATALOG NUMBER: ML104LSFLD2W1E-TIR1D55WFL-TL1RDMBB-200LM-3500K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	109	107	111	109	107	105	105	104	102	101	100	99	98	97	96	94			
2	109	104	101	97	107	103	99	96	99	97	94	96	94	92	94	92	90	89			
3	104	98	93	90	102	97	92	89	94	90	88	92	89	86	89	87	85	83			
4	99	92	87	83	97	91	86	83	89	85	82	87	84	81	85	82	80	78			
5	95	87	82	78	93	86	81	77	84	80	77	83	79	76	81	78	75	74			
6	90	82	77	73	89	81	76	72	80	75	72	79	75	71	77	74	71	70			
7	86	78	72	68	85	77	72	68	76	71	68	75	71	67	74	70	67	66			
8	83	74	68	64	81	73	68	64	72	67	64	71	67	64	70	66	64	62			
9	79	70	65	61	78	70	64	61	69	64	61	68	64	60	67	63	60	59			
10	76	67	61	58	75	66	61	58	65	61	57	65	60	57	64	60	57	56			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	581208
5°	573523
10°	544483
15°	490359
20°	421300
25°	343619
30°	218997
35°	111066
40°	55905
45°	21770
50°	6755
55°	2064
60°	0
65°	0
70°	0
75°	0
80°	0
85°	0

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 21770 cd/sqm



TEST NUMBER: P886038

CATALOG NUMBER: ML104LSFLD2W1E-TIR1D55WFL-TL1RDMBB-200LM-3500K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	27.1	13.4
10°-20°	66.6	32.9
20°-30°	69.8	34.5
30°-40°	31.3	15.5
40°-50°	7.1	3.5
50°-60°	0.6	0.3
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	163.5	80.8
0°-40°	194.8	96.2
0°-60°	202.4	100.0
0°-90°	202.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	202.4	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	294	
5°	290	27
15°	240	67
25°	158	70
35°	46	31
45°	8	7
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P886038

CATALOG NUMBER: ML104LSFLD2W1E-TIR1D55WFL-TL1RDMBB-200LM-3500K

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	294.5
2.5°	294.5
5°	289.5
7.5°	281.7
10°	271.7
12.5°	257.2
15°	240.0
17.5°	221.1
20°	200.6
22.5°	181.1
25°	157.8
27.5°	128.3
30°	96.1
32.5°	67.8
35°	46.1
37.5°	32.2
40°	21.7
42.5°	13.3
45°	7.8
47.5°	4.4
50°	2.2
52.5°	1.1
55°	0.6
57.5°	0.0
60°	0.0
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)