

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P886214

Luminaire Tested: ML204LSFL95FS1E-TIR1D55WFL-TL2RDSL-468LM-5000K

Issue Date: 6/20/2024


Test Information

Test Method: LM-79-2019
Report Number: P886214
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2402-314-84)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 6/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML204LSFL95FS1E-TIR1D55WFL-TL2RDSL-468LM-5000K
Description: 2IN ROUND ML FLEX, SELECTABLE CCT, WITH 55D TIR, METALLIC SILVER TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 95CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 552.0 lumens
Efficiency: N/A
Efficacy: 69.0 lumens/watt
Spacing Criteria (0/90/45): 0.85 / 0.85 / 0.81
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P886214

CATALOG NUMBER: ML204LSFL95FS1E-TIR1D55WFL-TL2RDSL-468LM-5000K

Luminous Intensity Polar Plot





TEST NUMBER: P886214

CATALOG NUMBER: ML204LSFL95FS1E-TIR1D55WFL-TL2RDSL-468LM-5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	109	107	111	109	107	105	105	103	102	101	100	99	98	97	96	94			
2	109	104	100	97	106	102	99	96	99	96	94	96	94	92	93	91	90	88			
3	103	97	93	89	102	96	92	88	93	90	87	91	88	86	89	86	84	83			
4	99	92	86	82	97	90	86	82	88	84	81	86	83	80	84	81	79	78			
5	94	86	81	77	92	85	80	76	83	79	76	82	78	75	80	77	74	73			
6	90	81	76	72	88	80	75	71	79	74	71	78	74	70	76	73	70	69			
7	86	77	71	67	84	76	71	67	75	70	67	74	69	66	73	69	66	65			
8	82	73	67	63	81	72	67	63	71	66	63	70	66	63	69	65	62	61			
9	78	69	63	60	77	68	63	60	68	63	59	67	62	59	66	62	59	58			
10	75	66	60	56	74	65	60	56	64	59	56	64	59	56	63	59	56	55			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	363621
5°	360651
10°	348740
15°	323735
20°	286254
25°	227335
30°	156954
35°	85045
40°	39481
45°	16327
50°	5987
55°	2495
60°	1875
65°	1167
70°	1443
75°	1906
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 16327 cd/sqm



TEST NUMBER: P886214

CATALOG NUMBER: ML204LSFL95FS1E-TIR1D55WFL-TL2RDSL-468LM-5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	68.5	12.4
10°-20°	176.2	31.9
20°-30°	188.4	34.1
30°-40°	93.2	16.9
40°-50°	20.8	3.8
50°-60°	3.2	0.6
60°-70°	1.1	0.2
70°-80°	0.7	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	433.1	78.5
0°-40°	526.2	95.3
0°-60°	550.3	99.7
0°-90°	552.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	552.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	737	
5°	728	68
15°	634	176
25°	418	188
35°	141	93
45°	23	21
55°	3	3
65°	1	1
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P886214

CATALOG NUMBER: ML204LSFL95FS1E-TIR1D55WFL-TL2RDSL-468LM-5000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	737.0
2.5°	736.0
5°	728.2
7.5°	714.6
10°	696.1
12.5°	666.9
15°	633.8
17.5°	594.8
20°	545.2
22.5°	485.8
25°	417.6
27.5°	346.6
30°	275.5
32.5°	208.3
35°	141.2
37.5°	92.5
40°	61.3
42.5°	38.9
45°	23.4
47.5°	13.6
50°	7.8
52.5°	4.9
55°	2.9
57.5°	1.9
60°	1.9
62.5°	1.0
65°	1.0
67.5°	1.0
70°	1.0
72.5°	1.0
75°	1.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)