

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P886217

Luminaire Tested: ML204LSFL95FS1E-TIR1D55WFL-TL2RDSLb-468LM-3500K

Issue Date: 6/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P886217
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2402-314-87)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 6/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML204LSFL95FS1E-TIR1D55WFL-TL2RDSL B-468LM-3500K
Description: 2IN ROUND ML FLEX, SELECTABLE CCT, WITH 55D TIR, METALLIC SILVER BAFFLED TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 95CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 508.3 lumens
Efficiency: N/A
Efficacy: 63.5 lumens/watt
Spacing Criteria (0/90/45): 0.86 / 0.86 / 0.82
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P886217

CATALOG NUMBER: ML204LSFL95FS1E-TIR1D55WFL-TL2RDSL B-468LM-3500K

Luminous Intensity Polar Plot





TEST NUMBER: P886217

CATALOG NUMBER: ML204LSFL95FS1E-TIR1D55WFL-TL2RDSLb-468LM-3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	109	107	111	109	107	105	105	103	102	101	100	99	98	97	96	94			
2	109	104	100	97	106	102	99	96	99	96	94	96	94	92	93	91	90	88			
3	103	97	93	89	101	96	92	88	93	90	87	91	88	85	89	86	84	83			
4	99	91	86	82	97	90	85	82	88	84	81	86	83	80	84	81	79	77			
5	94	86	80	76	92	85	80	76	83	79	75	82	78	75	80	77	74	73			
6	89	81	75	71	88	80	75	71	79	74	71	77	73	70	76	73	70	68			
7	85	77	71	67	84	76	71	67	75	70	66	73	69	66	72	69	66	64			
8	81	72	67	63	80	72	66	63	71	66	62	70	65	62	69	65	62	61			
9	78	69	63	59	77	68	63	59	67	62	59	66	62	59	66	62	59	57			
10	74	65	60	56	73	65	60	56	64	59	56	63	59	56	63	58	55	54			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	327604
5°	325735
10°	316075
15°	294365
20°	262154
25°	208989
30°	146300
35°	81371
40°	37484
45°	15629
50°	6217
55°	2322
60°	1776
65°	1051
70°	1298
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 15629 cd/sqm



TEST NUMBER: P886217

CATALOG NUMBER: ML204LSFL95FS1E-TIR1D55WFL-TL2RDSL B-468LM-3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	61.9	12.2
10°-20°	160.2	31.5
20°-30°	173.6	34.2
30°-40°	87.8	17.3
40°-50°	20.1	4.0
50°-60°	3.3	0.6
60°-70°	1.0	0.2
70°-80°	0.4	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	395.8	77.9
0°-40°	483.6	95.1
0°-60°	507.0	99.7
0°-90°	508.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	508.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	664	
5°	658	62
15°	576	160
25°	384	174
35°	135	88
45°	22	20
55°	3	3
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P886217

CATALOG NUMBER: ML204LSFL95FS1E-TIR1D55WFL-TL2RDSLb-468LM-3500K

CANDELA DISTRIBUTION (FULL):

	0°
0°	664.0
2.5°	663.1
5°	657.7
7.5°	646.1
10°	630.9
12.5°	604.9
15°	576.3
17.5°	541.4
20°	499.3
22.5°	449.2
25°	383.9
27.5°	318.6
30°	256.8
32.5°	196.9
35°	135.1
37.5°	85.9
40°	58.2
42.5°	37.6
45°	22.4
47.5°	13.4
50°	8.1
52.5°	5.4
55°	2.7
57.5°	1.8
60°	1.8
62.5°	0.9
65°	0.9
67.5°	0.9
70°	0.9
72.5°	0.9
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)