

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P886496

Luminaire Tested: ML204LSFLD2W1E-TIR1D55WFL-TL2RDSL-400LM-3500K

Issue Date: 6/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P886496
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2402-314-84)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 6/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML204LSFLD2W1E-TIR1D55WFL-TL2RDSL-400LM-3500K
Description: 2IN ROUND ML FLEX, SELECTABLE CCT, WITH 55D TIR, METALLIC SILVER TRIM
Light Source: (1) D2W LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 409.3 lumens
Efficiency: N/A
Efficacy: 66.0 lumens/watt
Spacing Criteria (0/90/45): 0.85 / 0.85 / 0.81
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 6.2
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P886496

CATALOG NUMBER: ML204LSFLD2W1E-TIR1D55WFL-TL2RDSL-400LM-3500K

Luminous Intensity Polar Plot





TEST NUMBER: P886496

CATALOG NUMBER: ML204LSFLD2W1E-TIR1D55WFL-TL2RD5L-400LM-3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	109	107	111	109	107	105	105	103	102	101	100	99	98	97	96	94			
2	109	104	100	97	106	102	99	96	99	96	94	96	94	92	93	91	90	88			
3	103	97	93	89	102	96	92	88	93	90	87	91	88	86	89	86	84	83			
4	99	92	86	82	97	90	86	82	88	84	81	86	83	80	84	81	79	78			
5	94	86	81	77	92	85	80	76	83	79	76	82	78	75	80	77	74	73			
6	90	81	76	72	88	80	75	71	79	74	71	78	74	70	76	73	70	69			
7	86	77	71	67	84	76	71	67	75	70	67	74	69	66	73	69	66	65			
8	82	73	67	63	81	72	67	63	71	66	63	70	66	63	69	65	62	61			
9	78	69	63	60	77	68	63	60	68	63	59	67	62	59	66	62	59	58			
10	75	66	60	56	74	65	60	56	64	59	56	64	59	56	63	59	56	55			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	269632
5°	267443
10°	258561
15°	240017
20°	212223
25°	168596
30°	116391
35°	63061
40°	29305
45°	12071
50°	4452
55°	1892
60°	1381
65°	817
70°	1010
75°	1334
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 12071 cd/sqm



TEST NUMBER: P886496

CATALOG NUMBER: ML204LSFLD2W1E-TIR1D55WFL-TL2RDSL-400LM-3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	50.8	12.4
10°-20°	130.6	31.9
20°-30°	139.7	34.1
30°-40°	69.1	16.9
40°-50°	15.5	3.8
50°-60°	2.4	0.6
60°-70°	0.8	0.2
70°-80°	0.5	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	321.1	78.5
0°-40°	390.2	95.3
0°-60°	408.0	99.7
0°-90°	409.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	409.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	546	
5°	540	51
15°	470	131
25°	310	140
35°	105	69
45°	17	15
55°	2	2
65°	1	1
75°	1	0
85°	0	0
90°	0	



TEST NUMBER: P886496

CATALOG NUMBER: ML204LSFLD2W1E-TIR1D55WFL-TL2RDSL-400LM-3500K

CANDELA DISTRIBUTION (FULL):

0°	
0°	546.5
2.5°	545.7
5°	540.0
7.5°	529.8
10°	516.1
12.5°	494.5
15°	469.9
17.5°	441.1
20°	404.2
22.5°	360.2
25°	309.7
27.5°	257.0
30°	204.3
32.5°	154.5
35°	104.7
37.5°	68.6
40°	45.5
42.5°	28.9
45°	17.3
47.5°	10.1
50°	5.8
52.5°	3.6
55°	2.2
57.5°	1.4
60°	1.4
62.5°	0.7
65°	0.7
67.5°	0.7
70°	0.7
72.5°	0.7
75°	0.7
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)