

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: HALO

Report Number: P601404

Luminaire Tested: **ML4DM08LSFL95FS1E - TIR4D40FL - TL43R2G\_ TL44S2G\_ 3500K**

Issue Date: 7/29/2022

Tested By:

Approved By:



Cooper Lighting Solutions laboratories have been accredited by National Voluntary Laboratory Accreditation Program (NVLAP) that it adheres to the requirements of ISO/IEC 17025:2005 and appropriate IESNA test methods. This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the Federal Government. Results contained in this report are valid for luminaire sample tested, as supplied by requestor. Information related to the luminaire tested has been supplied by requestor and can affect the validity of the test results. Report shall not be reproduced except in full without approval of Cooper Lighting Solutions Lighting Laboratory. Test performed at address noted above.

**Test Information**

Test Method: LM-79-08  
 Report Number: P601404  
 Test Lab: COOPER LIGHTING SOLUTIONS  
 Issue Date: 7/29/2022  
 Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
 Product Line: HALO  
 Catalog Number: ML4DM08LSFL95FS1E - TIR4D40FL - TL43R2G\_ TL44S2G\_ 3500K  
 Description: DIRECT MOUNT, 40D OPTIC, DIFFUSE CLEAR LENS TRIM  
 Light Source: (1) SELECTABLE LUMEN LED 95CRI / 3500K CCT  
 Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
 Luminaire Lumens: 1000.5 lumens  
 Efficiency: N/A  
 Efficacy: 97.1 lumens/watt  
 Spacing Criteria (0/90/45): 0.67 / 0.67 / 0.63  
 Luminous Opening: Circular (Dia: 0.21' x H: 0')  
 CIE Type: Direct


Input Watts (W): 10.3  
 Input Voltage (V): NR  
 Input Current (Ain): NR  
 Voltage Rise (V): NR  
 Power Factor: NR  
 Total Harmonic Distortion (THDi): NR  
 Frequency (hertz): 60  
 Stabilization Time: NR  
 Operation Time: NR  
 Ambient Temperature (°C): NR  
 Test Distance: 25 FT



Meas		Calibration Due Date	
Instrument	Identificatio		
Photometer	GONIO 1 11111111	4/22/2021	10/22/2021
Power Meter	XITRON 2801 IN0197	12/1/2020	12/1/2021
AC Power Source	CHROMA 61505 IN0196	12/1/2020	12/1/2021
DC Power Supply	AGILENT E3634A IN0198	11/30/2020	11/30/2021
Room Thermometer	ONSET IN0143	12/1/2020	12/1/2021

TEST NUMBER: P601404  
CATALOG NUMBER: ML4DM08LSFL95FS1E - TIR4D40FL - TL43R2G\_ TL44S2G\_ 3500K

### Luminous Intensity Polar Plot



TEST NUMBER: P601404

CATALOG NUMBER: ML4DM08LSFL95FS1E - TIR4D40FL - TL43R2G\_ TL44S2G\_ 3500K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95
2	109	105	102	99	107	104	100	98	100	98	95	97	95	93	95	93	92	90
3	105	99	95	92	103	98	94	91	95	92	89	93	90	88	91	89	87	85
4	101	94	89	86	99	93	89	85	91	87	84	89	86	83	87	85	82	81
5	97	89	84	81	95	88	84	80	87	83	80	85	82	79	84	81	78	77
6	93	85	80	76	91	84	79	76	83	79	75	82	78	75	80	77	75	73
7	89	81	76	72	88	80	76	72	79	75	72	78	74	71	77	74	71	70
8	86	77	72	69	85	77	72	69	76	72	68	75	71	68	74	71	68	67
9	82	74	69	66	81	74	69	66	73	68	65	72	68	65	71	68	65	64
10	79	71	66	63	78	71	66	63	70	66	63	69	65	62	69	65	62	61

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	646213
5°	628206
10°	574196
15°	485714
20°	353840
25°	205038
30°	105228
35°	55123
40°	29720
45°	15808
50°	9334
55°	4900
60°	2400
65°	1868
70°	1200
75°	0
80°	0
85°	0

TEST NUMBER: P601404  
 CATALOG NUMBER: ML4DM08LSFL95FS1E - TIR4D40FL - TL43R2G\_ TL44S2G\_ 3500K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	182.7	18.3
10°-20°	403.1	40.3
20°-30°	277.2	27.7
30°-40°	96.1	9.6
40°-50°	29.8	3.0
50°-60°	9.0	0.9
60°-70°	2.2	0.2
70°-80°	0.5	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	863.0	86.3
0°-40°	959.1	95.9
0°-60°	997.8	99.7
0°-90°	1000.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1000.5	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	2046	
5°	1982	183
15°	1486	403
25°	588	277
35°	143	96
45°	35	30
55°	9	9
65°	2	2
75°	0	1
85°	0	0
90°	0	

TEST NUMBER: P601404  
CATALOG NUMBER: ML4DM08LSFL95FS1E - TIR4D40FL - TL43R2G\_ TL44S2G\_ 3500K

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	2046.5
1°	2050.3
2°	2042.7
3°	2027.5
4°	2003.4
5°	1981.9
6°	1950.3
7°	1913.6
8°	1869.3
9°	1833.8
10°	1790.8
11°	1730.1
12°	1683.2
13°	1620.0
14°	1556.7
15°	1485.8
17.5°	1280.8
20°	1053.0
22.5°	808.7
25°	588.5
27.5°	417.6
30°	288.6
32.5°	202.5
35°	143.0
37.5°	102.5
40°	72.1
42.5°	50.6
45°	35.4
47.5°	25.3
50°	19.0
52.5°	13.9
55°	8.9
57.5°	6.3
60°	3.8
62.5°	2.5
65°	2.5
67.5°	1.3
70°	1.3
72.5°	1.3
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

  
NVLAP Lab Code: 200050-0



TEST NUMBER: P601404  
CATALOG NUMBER: ML4DM08LSFL95FS1E - TIR4D40FL - TL43R2G\_ TL44S2G\_ 3500K

CANDELA DISTRIBUTION (continued):



(END OF REPORT)