

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: HALO

Report Number: P601420

Luminaire Tested: **ML4DM08LSWFL95FS1E - TIR4D55WFL - TL41R\_ TL42S\_ 4000K**

Issue Date: 7/29/2022

Tested By:

Approved By:



Cooper Lighting Solutions laboratories have been accredited by National Voluntary Laboratory Accreditation Program (NVLAP) that it adheres to the requirements of ISO/IEC 17025:2005 and appropriate IESNA test methods. This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the Federal Government. Results contained in this report are valid for luminaire sample tested, as supplied by requestor. Information related to the luminaire tested has been supplied by requestor and can affect the validity of the test results. Report shall not be reproduced except in full without approval of Cooper Lighting Solutions Lighting Laboratory. Test performed at address noted above.

**Test Information**

Test Method: LM-79-08  
 Report Number: P601420  
 Test Lab: COOPER LIGHTING SOLUTIONS  
 Issue Date: 7/29/2022  
 Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
 Product Line: HALO  
 Catalog Number: ML4DM08LSWFL95FS1E - TIR4D55WFL - TL41R\_TL42S\_4000K  
 Description: DIRECT MOUNT, 55D OPTIC, OPEN TRIM  
 Light Source: (1) SELECTABLE LUMEN LED 95CRI / 4000K CCT  
 Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
 Luminaire Lumens: 1063.8 lumens  
 Efficiency: N/A  
 Efficacy: 103.3 lumens/watt  
 Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.84  
 Luminous Opening: Circular (Dia: 0.21' x H: 0')  
 CIE Type: Direct


Input Watts (W): 10.3  
 Input Voltage (V): NR  
 Input Current (Ain): NR  
 Voltage Rise (V): NR  
 Power Factor: NR  
 Total Harmonic Distortion (THDi): NR  
 Frequency (hertz): 60  
 Stabilization Time: NR  
 Operation Time: NR  
 Ambient Temperature (°C): NR  
 Test Distance: 25 FT



Meas		Calibration Due Date	
Instrument	Identificatio		
Photometer	GONIO 1 11111111	4/22/2021	10/22/2021
Power Meter	XITRON 2801 IN0197	12/1/2020	12/1/2021
AC Power Source	CHROMA 61505 IN0196	12/1/2020	12/1/2021
DC Power Supply	AGILENT E3634A IN0198	11/30/2020	11/30/2021
Room Thermometer	ONSET IN0143	12/1/2020	12/1/2021

TEST NUMBER: P601420  
CATALOG NUMBER: ML4DM08LSWFL95FS1E - TIR4D55WFL - TL41R\_TL42S\_4000K

### Luminous Intensity Polar Plot



TEST NUMBER: P601420  
 CATALOG NUMBER: ML4DM08LSWFL95FS1E - TIR4D55WFL - TL41R\_ TL42S\_ 4000K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				20
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	114	111	109	107	111	109	107	105	105	103	102	101	100	99	98	97	96	94	94	94	94
2	109	104	100	97	106	102	99	96	99	96	94	96	94	92	93	92	90	88	88	88	88
3	104	98	93	89	102	96	92	88	94	90	87	91	88	86	89	86	84	83	83	83	83
4	99	92	86	82	97	91	86	82	88	84	81	86	83	80	85	82	79	78	78	78	78
5	94	86	81	77	93	85	80	76	84	79	76	82	78	75	80	77	74	73	73	73	73
6	90	81	76	72	88	81	75	71	79	74	71	78	74	71	76	73	70	69	69	69	69
7	86	77	71	67	84	76	71	67	75	70	67	74	70	66	73	69	66	65	65	65	65
8	82	73	67	63	81	72	67	63	71	66	63	70	66	63	69	65	62	61	61	61	61
9	78	69	63	60	77	69	63	60	68	63	59	67	62	59	66	62	59	58	58	58	58
10	75	66	60	56	74	65	60	56	64	59	56	64	59	56	63	59	56	55	55	55	55

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	419020
5°	419036
10°	413364
15°	398823
20°	362140
25°	300049
30°	203345
35°	99492
40°	44641
45°	16299
50°	6779
55°	2753
60°	821
65°	0
70°	0
75°	0
80°	0
85°	0

TEST NUMBER: P601420  
 CATALOG NUMBER: ML4DM08LSWFL95FS1E - TIR4D55WFL - TL41R\_ TL42S\_ 4000K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	125.0	11.8
10°-20°	338.3	31.8
20°-30°	384.0	36.1
30°-40°	175.5	16.5
40°-50°	35.2	3.3
50°-60°	5.2	0.5
60°-70°	0.5	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	847.4	79.7
0°-40°	1022.9	96.2
0°-60°	1063.3	100.0
0°-90°	1063.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1063.8	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1327	
5°	1322	125
15°	1220	338
25°	861	384
35°	258	176
45°	36	35
55°	5	5
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P601420  
CATALOG NUMBER: ML4DM08LSWFL95FS1E - TIR4D55WFL - TL41R\_ TL42S\_ 4000K

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1327.0
2.5°	1320.7
5°	1322.0
7.5°	1308.1
10°	1289.2
12.5°	1259.0
15°	1220.0
17.5°	1154.5
20°	1077.7
22.5°	982.0
25°	861.2
27.5°	718.9
30°	557.7
32.5°	392.8
35°	258.1
37.5°	168.7
40°	108.3
42.5°	68.0
45°	36.5
47.5°	21.4
50°	13.8
52.5°	8.8
55°	5.0
57.5°	2.5
60°	1.3
62.5°	1.3
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)