

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P886620

Luminaire Tested: ML310LSFL95FS1E-TIR4D55WFL-TL3RDMW-850LM-4000K

Issue Date: 7/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P886620
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2402-314-7)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 7/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML310LSFL95FS1E-TIR4D55WFL-TL3RDMW-850LM-4000K
Description: 3IN ROUND ML FLEX, SELECTABLE CCT, WITH 55D TIR, MATTE WHITE TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 95CRI / 4000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1149.8 lumens
Efficiency: N/A
Efficacy: 84.5 lumens/watt
Spacing Criteria (0/90/45): 0.82 / 0.82 / 0.76
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 13.6
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P886620
CATALOG NUMBER: ML310LSFL95FS1E-TIR4D55WFL-TL3RDMW-850LM-4000K

Luminous Intensity Polar Plot





TEST NUMBER: P886620
 CATALOG NUMBER: ML310LSFL95FS1E-TIR4D55WFL-TL3RDMW-850LM-4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	109	106	111	109	107	105	105	103	102	101	100	99	98	97	96	94			
2	109	104	100	97	106	102	99	96	99	96	94	96	94	92	93	91	90	88			
3	104	98	93	89	102	96	92	89	94	90	87	91	88	86	89	87	85	83			
4	99	92	87	83	97	91	86	83	89	85	82	87	83	81	85	82	80	78			
5	95	87	82	78	93	86	81	77	84	80	77	83	79	76	81	78	75	74			
6	91	82	77	73	89	82	76	73	80	76	72	79	75	72	78	74	71	70			
7	87	78	73	69	85	78	72	69	76	72	68	75	71	68	74	70	68	66			
8	83	74	69	65	82	74	69	65	73	68	65	72	68	65	71	67	64	63			
9	80	71	65	62	79	70	65	62	70	65	62	69	64	61	68	64	61	60			
10	76	68	62	59	76	67	62	59	66	62	59	66	61	58	65	61	58	57			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	390210
5°	382213
10°	359156
15°	327925
20°	288845
25°	232030
30°	117588
35°	40823
40°	12624
45°	6233
50°	6175
55°	6537
60°	6578
65°	6745
70°	7052
75°	6778
80°	6314
85°	5032

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 77.5°
 Luminance: 7092 cd/sqm



TEST NUMBER: P886620

CATALOG NUMBER: ML310LSFL95FS1E-TIR4D55WFL-TL3RDMW-850LM-4000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	161.8	14.1
10°-20°	402.0	35.0
20°-30°	415.0	36.1
30°-40°	114.2	9.9
40°-50°	17.9	1.6
50°-60°	14.9	1.3
60°-70°	12.9	1.1
70°-80°	8.4	0.7
80°-90°	2.6	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	978.8	85.1
0°-40°	1093.0	95.1
0°-60°	1125.8	97.9
0°-90°	1149.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1149.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1780	
5°	1736	162
15°	1444	402
25°	959	415
35°	152	114
45°	20	18
55°	17	15
65°	13	13
75°	8	8
85°	2	3
90°	0	



TEST NUMBER: P886620

CATALOG NUMBER: ML310LSFL95FS1E-TIR4D55WFL-TL3RDMW-850LM-4000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	1779.5
2.5°	1772.5
5°	1736.4
7.5°	1682.2
10°	1613.0
12.5°	1532.7
15°	1444.5
17.5°	1346.2
20°	1237.8
22.5°	1121.5
25°	959.0
27.5°	744.3
30°	464.4
32.5°	270.8
35°	152.5
37.5°	81.3
40°	44.1
42.5°	23.1
45°	20.1
47.5°	19.1
50°	18.1
52.5°	17.1
55°	17.1
57.5°	16.0
60°	15.0
62.5°	14.0
65°	13.0
67.5°	12.0
70°	11.0
72.5°	9.0
75°	8.0
77.5°	7.0
80°	5.0
82.5°	4.0
85°	2.0
87.5°	1.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)