

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P887063

Luminaire Tested: ML412LSFL9FS1E-TIR4D55WFL-TL4RDSL-1200LM-4000K

Issue Date: 7/9/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P887063  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2402-314-43)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 7/9/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: HALO  
Catalog Number: ML412LSFL9FS1E-TIR4D55WFL-TL4RDSL-1200LM-4000K  
Description: 4IN ROUND ML FLEX, SELECTABLE CCT, WITH 55D TIR, METALLIC SILVER TRIM  
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 4000K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1552.0 lumens  
Efficiency: N/A  
Efficacy: 88.2 lumens/watt  
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.77  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct


Input Watts (W): 17.6  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



TEST NUMBER: P887063

CATALOG NUMBER: ML412LSFL9FS1E-TIR4D55WFL-TL4RDSL-1200LM-4000K

### Luminous Intensity Polar Plot





TEST NUMBER: P887063

CATALOG NUMBER: ML412LSFL9FS1E-TIR4D55WFL-TL4RDSL-1200LM-4000K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									20									20
RC	80									70									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																														
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																												
1	114	112	109	107	112	109	107	106	105	104	102	102	101	99	98	97	96	95																												
2	109	105	101	98	107	103	100	97	100	97	95	97	95	93	94	93	91	90																												
3	105	99	94	91	103	98	93	90	95	92	89	93	90	87	90	88	86	85																												
4	100	93	89	85	98	92	88	84	90	86	83	88	85	82	87	84	81	80																												
5	96	88	83	80	94	88	83	79	86	82	79	84	81	78	83	80	77	76																												
6	92	84	79	75	90	83	78	75	82	77	74	80	77	74	79	76	73	72																												
7	88	80	74	71	87	79	74	71	78	73	70	77	73	70	76	72	69	68																												
8	84	76	71	67	83	75	70	67	74	70	67	73	69	66	72	69	66	65																												
9	81	72	67	64	80	72	67	64	71	66	63	70	66	63	69	66	63	62																												
10	78	69	64	61	77	69	64	60	68	63	60	67	63	60	67	63	60	59																												

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	315740
5°	302014
10°	277125
15°	251614
20°	222213
25°	181635
30°	108829
35°	32133
40°	6940
45°	1744
50°	1266
55°	946
60°	814
65°	642
70°	397
75°	524
80°	781
85°	0

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 1744 cd/sqm



TEST NUMBER: P887063

CATALOG NUMBER: ML412LSFL9FS1E-TIR4D55WFL-TL4RDSL-1200LM-4000K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	225.7	14.5
10°-20°	549.3	35.4
20°-30°	589.0	38.0
30°-40°	169.2	10.9
40°-50°	10.7	0.7
50°-60°	4.3	0.3
60°-70°	2.4	0.2
70°-80°	1.2	0.1
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1364.0	87.9
0°-40°	1533.2	98.8
0°-60°	1548.2	99.8
0°-90°	1552.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1552.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	2560	
5°	2439	226
15°	1970	549
25°	1335	589
35°	213	169
45°	10	11
55°	4	4
65°	2	2
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P887063

CATALOG NUMBER: ML412LSFL9FS1E-TIR4D55WFL-TL4RDSL-1200LM-4000K

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	2559.8
2.5°	2543.2
5°	2439.2
7.5°	2326.4
10°	2212.6
12.5°	2092.0
15°	1970.4
17.5°	1839.9
20°	1692.9
22.5°	1524.8
25°	1334.6
27.5°	1106.8
30°	764.1
32.5°	406.9
35°	213.4
37.5°	106.1
40°	43.1
42.5°	14.4
45°	10.0
47.5°	7.7
50°	6.6
52.5°	5.5
55°	4.4
57.5°	4.4
60°	3.3
62.5°	3.3
65°	2.2
67.5°	2.2
70°	1.1
72.5°	1.1
75°	1.1
77.5°	1.1
80°	1.1
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)