

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P640547

Luminaire Tested: ML5612LSFL4097FS1E - 591WB - 600LM - 3000K

Issue Date: 2/17/2023

**Test Information**

Test Method: LM-79-2019  
Report Number: P640547  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-24)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/17/2023  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: HALO  
Catalog Number: ML5612LSFL4097FS1E - 591WB - 600LM - 3000K  
Description: ML56 RR, 40D TIR OPTIC, 5" DEADFRONT TRIM  
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 3000K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 997.1 lumens  
Efficiency: N/A  
Efficacy: 96.8 lumens/watt  
Spacing Criteria (0/90/45): 0.64 / 0.64 / 0.69  
Luminous Opening: Circular (Dia: 0.42' x H: 0')  
CIE Type: Direct


Input Watts (W): 10.3  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



TEST NUMBER: P640547

CATALOG NUMBER: ML5612LSFL4097FS1E - 591WB - 600LM - 3000K

### Luminous Intensity Polar Plot





TEST NUMBER: P640547

CATALOG NUMBER: ML5612LSFL4097FS1E - 591WB - 600LM - 3000K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	114	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	94																			
2	108	103	99	96	106	101	98	95	98	95	93	95	93	91	93	91	89	87																			
3	103	96	91	88	101	95	90	87	92	89	85	90	87	84	88	85	83	81																			
4	98	90	85	81	96	89	84	80	87	83	79	85	81	78	83	80	77	76																			
5	93	85	79	75	91	84	78	74	82	77	74	80	76	73	79	75	72	71																			
6	88	80	74	70	87	79	73	69	77	73	69	76	72	69	75	71	68	67																			
7	84	75	69	65	83	75	69	65	73	68	65	72	68	64	71	67	64	63																			
8	80	71	65	61	79	71	65	61	70	65	61	69	64	61	68	63	60	59																			
9	77	67	62	58	76	67	62	58	66	61	58	65	61	57	64	60	57	56																			
10	74	64	59	55	73	64	58	55	63	58	55	62	58	54	61	57	54	53																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	128082
5°	123927
10°	108110
15°	88852
20°	69214
25°	52418
30°	37947
35°	26049
40°	17034
45°	10740
50°	6226
55°	2642
60°	1800
65°	1139
70°	600
75°	519
80°	773
85°	815

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 10740 cd/sqm



TEST NUMBER: P640547

CATALOG NUMBER: ML5612LSFL4097FS1E - 591WB - 600LM - 3000K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	142.2	14.3
10°-20°	300.2	30.1
20°-30°	276.0	27.7
30°-40°	171.3	17.2
40°-50°	76.8	7.7
50°-60°	21.4	2.1
60°-70°	6.4	0.6
70°-80°	1.9	0.2
80°-90°	1.0	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	718.3	72.0
0°-40°	889.6	89.2
0°-60°	987.7	99.1
0°-90°	997.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	997.1	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1622	
5°	1564	142
15°	1087	300
25°	602	276
35°	270	171
45°	96	77
55°	19	21
65°	6	6
75°	2	2
85°	1	1
90°	0	



TEST NUMBER: P640547

CATALOG NUMBER: ML5612LSFL4097FS1E - 591WB - 600LM - 3000K

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1622.5
2.5°	1611.1
5°	1563.9
7.5°	1470.3
10°	1348.7
12.5°	1216.7
15°	1087.2
17.5°	952.5
20°	823.9
22.5°	706.7
25°	601.8
27.5°	503.8
30°	416.3
32.5°	336.7
35°	270.3
37.5°	212.5
40°	165.3
42.5°	127.7
45°	96.2
47.5°	70.8
50°	50.7
52.5°	31.5
55°	19.2
57.5°	14.9
60°	11.4
62.5°	8.7
65°	6.1
67.5°	4.4
70°	2.6
72.5°	1.7
75°	1.7
77.5°	1.7
80°	1.7
82.5°	0.9
85°	0.9
87.5°	0.9
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)