

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P640584

Luminaire Tested: ML5612LSFL4097FS1E - 592SC - 900LM - 4000K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P640584
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-25)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5612LSFL4097FS1E - 592SC - 900LM - 4000K
Description: ML56 RR, 40D TIR OPTIC, 5" SPECULAR CLEAR TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1415.2 lumens
Efficiency: N/A
Efficacy: 106.4 lumens/watt
Spacing Criteria (0/90/45): 0.64 / 0.64 / 0.69
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct

Input Watts (W): 13.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P640584
CATALOG NUMBER: ML5612LSFL4097FS1E - 592SC - 900LM - 4000K

Luminous Intensity Polar Plot





TEST NUMBER: P640584
 CATALOG NUMBER: ML5612LSFL4097FS1E - 592SC - 900LM - 4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				
1	114	111	109	107	111	109	107	105	105	103	102	101	100	99	98	97	96	94				
2	108	104	100	97	106	102	99	96	99	96	94	96	94	92	93	91	90	88				
3	103	97	92	89	101	96	91	88	93	90	87	91	88	85	89	86	84	82				
4	98	91	86	82	97	90	85	81	88	84	80	86	82	80	84	81	79	77				
5	94	86	80	76	92	85	80	76	83	79	75	81	78	75	80	77	74	72				
6	89	81	75	71	88	80	75	71	79	74	70	77	73	70	76	72	70	68				
7	85	77	71	67	84	76	70	67	75	70	66	73	69	66	72	69	66	64				
8	82	72	67	63	80	72	67	63	71	66	63	70	65	62	69	65	62	61				
9	78	69	63	59	77	68	63	59	67	63	59	67	62	59	66	62	59	57				
10	75	65	60	56	74	65	60	56	64	59	56	63	59	56	63	59	56	55				

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	188977
5°	182717
10°	159364
15°	131439
20°	101539
25°	76205
30°	54865
35°	37430
40°	23403
45°	13296
50°	4728
55°	2739
60°	1563
65°	467
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 13296 cd/sqm



TEST NUMBER: P640584

CATALOG NUMBER: ML5612LSFL4097FS1E - 592SC - 900LM - 4000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	209.6	14.8
10°-20°	443.2	31.3
20°-30°	401.9	28.4
30°-40°	245.5	17.3
40°-50°	92.8	6.6
50°-60°	18.8	1.3
60°-70°	3.3	0.2
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1054.7	74.5
0°-40°	1300.2	91.9
0°-60°	1411.9	99.8
0°-90°	1415.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1415.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2394	
5°	2306	210
15°	1608	443
25°	875	402
35°	388	245
45°	119	93
55°	20	19
65°	2	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P640584
CATALOG NUMBER: ML5612LSFL4097FS1E - 592SC - 900LM - 4000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	2393.9
2.5°	2375.3
5°	2305.8
7.5°	2168.0
10°	1988.1
12.5°	1800.7
15°	1608.3
17.5°	1406.0
20°	1208.7
22.5°	1031.3
25°	874.9
27.5°	732.2
30°	601.9
32.5°	486.5
35°	388.4
37.5°	302.8
40°	227.1
42.5°	171.3
45°	119.1
47.5°	67.0
50°	38.5
52.5°	27.3
55°	19.9
57.5°	13.7
60°	9.9
62.5°	6.2
65°	2.5
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)