

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P640650

Luminaire Tested: ML5612LSFL4097FS1E - 593WB - 1200LM - 5000K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P640650
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-28)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5612LSFL4097FS1E - 593WB - 1200LM - 5000K
Description: ML56 RR, 40D TIR OPTIC, 5" WHITE BAFFLE TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1706.3 lumens
Efficiency: N/A
Efficacy: 103.4 lumens/watt
Spacing Criteria (0/90/45): 0.64 / 0.64 / 0.69
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct

Input Watts (W): 16.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P640650
CATALOG NUMBER: ML5612LSFL4097FS1E - 593WB - 1200LM - 5000K

Luminous Intensity Polar Plot





TEST NUMBER: P640650

CATALOG NUMBER: ML5612LSFL4097FS1E - 593WB - 1200LM - 5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	114	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	94																			
2	108	103	99	96	106	102	98	95	98	95	93	95	93	91	93	91	89	87																			
3	103	96	92	88	101	95	91	87	92	89	86	90	87	84	88	85	83	81																			
4	98	90	85	81	96	89	84	80	87	83	79	85	82	79	83	80	78	76																			
5	93	85	79	75	92	84	79	75	82	78	74	81	77	73	79	76	73	71																			
6	89	80	74	70	87	79	74	70	78	73	69	76	72	69	75	71	68	67																			
7	85	76	70	66	83	75	69	66	74	69	65	73	68	65	71	67	64	63																			
8	81	72	66	62	80	71	66	62	70	65	61	69	64	61	68	64	61	60																			
9	77	68	62	58	76	67	62	58	66	62	58	66	61	58	65	61	58	56																			
10	74	65	59	55	73	64	59	55	63	58	55	63	58	55	62	58	55	53																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	221398
5°	214264
10°	187002
15°	153701
20°	119761
25°	91326
30°	66141
35°	45168
40°	28174
45°	16768
50°	6644
55°	4335
60°	3079
65°	1961
70°	1731
75°	1830
80°	2046
85°	2717

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 16768 cd/sqm



TEST NUMBER: P640650

CATALOG NUMBER: ML5612LSFL4097FS1E - 593WB - 1200LM - 5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	245.9	14.4
10°-20°	519.3	30.4
20°-30°	479.9	28.1
30°-40°	296.6	17.4
40°-50°	115.0	6.7
50°-60°	29.5	1.7
60°-70°	11.5	0.7
70°-80°	5.9	0.3
80°-90°	2.7	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1245.0	73.0
0°-40°	1541.7	90.4
0°-60°	1686.2	98.8
0°-90°	1706.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1706.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2805	
5°	2704	246
15°	1881	519
25°	1048	480
35°	469	297
45°	150	115
55°	32	30
65°	10	11
75°	6	6
85°	3	3
90°	0	



TEST NUMBER: P640650

CATALOG NUMBER: ML5612LSFL4097FS1E - 593WB - 1200LM - 5000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	2804.6
2.5°	2786.5
5°	2703.9
7.5°	2543.2
10°	2332.9
12.5°	2104.6
15°	1880.7
17.5°	1647.9
20°	1425.6
22.5°	1225.8
25°	1048.5
27.5°	878.8
30°	725.6
32.5°	587.4
35°	468.7
37.5°	368.0
40°	273.4
42.5°	208.8
45°	150.2
47.5°	84.1
50°	54.1
52.5°	40.6
55°	31.5
57.5°	24.0
60°	19.5
62.5°	15.0
65°	10.5
67.5°	7.5
70°	7.5
72.5°	6.0
75°	6.0
77.5°	4.5
80°	4.5
82.5°	3.0
85°	3.0
87.5°	1.5
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)