

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P641081

Luminaire Tested: ML5612LSNFL2597FS1E - 692H - 1200LM - 2700K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P641081
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-15)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5612LSNFL2597FS1E - 692H - 1200LM - 2700K
Description: ML56 RR, 25D TIR OPTIC, 6" HAZE TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1401.3 lumens
Efficiency: N/A
Efficacy: 84.9 lumens/watt
Spacing Criteria (0/90/45): 0.43 / 0.43 / 0.44
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 16.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P641081
CATALOG NUMBER: ML5612LSNFL2597FS1E - 692H - 1200LM - 2700K

Luminous Intensity Polar Plot





TEST NUMBER: P641081

CATALOG NUMBER: ML5612LSNFL2597FS1E - 692H - 1200LM - 2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	114	111	109	106	111	109	107	105	105	103	102	101	100	99	98	97	96	94																			
2	108	104	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88																			
3	103	97	92	88	101	96	91	88	93	89	86	91	87	85	88	86	84	82																			
4	98	91	86	82	96	90	85	81	88	84	80	86	82	79	84	81	78	77																			
5	94	86	80	76	92	85	79	76	83	78	75	81	77	74	80	76	74	72																			
6	89	81	75	71	88	80	75	71	79	74	70	77	73	70	76	72	69	68																			
7	85	77	71	67	84	76	70	67	75	70	66	73	69	66	72	69	66	64																			
8	82	73	67	63	81	72	67	63	71	66	63	70	66	62	69	65	62	61																			
9	78	69	64	60	77	69	63	60	68	63	60	67	63	59	66	62	59	58																			
10	75	66	61	57	74	66	60	57	65	60	57	64	60	57	63	59	56	55																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	200461
5°	182836
10°	134355
15°	77674
20°	48246
25°	38754
30°	31695
35°	25638
40°	20231
45°	15257
50°	7889
55°	2275
60°	1447
65°	856
70°	417
75°	275
80°	410
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 15257 cd/sqm



TEST NUMBER: P641081

CATALOG NUMBER: ML5612LSNFL2597FS1E - 692H - 1200LM - 2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	287.6	20.5
10°-20°	392.8	28.0
20°-30°	295.7	21.1
30°-40°	240.2	17.1
40°-50°	146.6	10.5
50°-60°	30.2	2.2
60°-70°	6.5	0.5
70°-80°	1.5	0.1
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	976.1	69.7
0°-40°	1216.3	86.8
0°-60°	1393.1	99.4
0°-90°	1401.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1401.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3657	
5°	3322	288
15°	1369	393
25°	641	296
35°	383	240
45°	197	147
55°	24	30
65°	7	6
75°	1	2
85°	0	0
90°	0	



TEST NUMBER: P641081

CATALOG NUMBER: ML5612LSNFL2597FS1E - 692H - 1200LM - 2700K

CANDELA DISTRIBUTION (FULL):

0°	
0°	3656.7
2.5°	3578.8
5°	3322.5
7.5°	2913.0
10°	2413.6
12.5°	1858.7
15°	1368.6
17.5°	1025.2
20°	827.0
22.5°	720.0
25°	640.7
27.5°	568.1
30°	500.7
32.5°	441.2
35°	383.1
37.5°	330.3
40°	282.7
42.5°	240.4
45°	196.8
47.5°	142.7
50°	92.5
52.5°	43.6
55°	23.8
57.5°	17.2
60°	13.2
62.5°	9.2
65°	6.6
67.5°	2.6
70°	2.6
72.5°	1.3
75°	1.3
77.5°	1.3
80°	1.3
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)