

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P641207

Luminaire Tested: ML5612LSNFL2597FS1E - 694WB - 600LM - 3000K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P641207
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-21)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5612LSNFL2597FS1E - 694WB - 600LM - 3000K
Description: ML56 RR, 25D TIR OPTIC, 6" WHITE GIMBAL TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 957.8 lumens
Efficiency: N/A
Efficacy: 93.0 lumens/watt
Spacing Criteria (0/90/45): 0.42 / 0.42 / 0.43
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 10.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P641207
CATALOG NUMBER: ML5612LSNFL2597FS1E - 694WB - 600LM - 3000K

Luminous Intensity Polar Plot





TEST NUMBER: P641207

CATALOG NUMBER: ML5612LSNFL2597FS1E - 694WB - 600LM - 3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94	92	92	92	92
2	107	102	97	94	105	100	96	93	97	93	91	94	91	89	91	89	87	85	85	85	85
3	101	94	89	85	99	93	88	84	90	86	83	88	84	81	85	83	80	78	78	78	78
4	96	88	82	78	94	87	81	77	85	80	76	82	78	75	81	77	74	73	73	73	73
5	91	82	76	72	89	81	76	71	79	74	71	78	73	70	76	72	69	68	68	68	68
6	87	77	71	67	85	76	71	66	75	70	66	74	69	66	72	68	65	64	64	64	64
7	82	73	67	62	81	72	66	62	71	66	62	70	65	62	69	64	61	60	60	60	60
8	79	69	63	59	77	69	63	59	67	62	58	66	62	58	65	61	58	57	57	57	57
9	75	66	60	56	74	65	60	56	64	59	55	63	59	55	62	58	55	54	54	54	54
10	72	63	57	53	71	62	57	53	61	56	53	61	56	53	60	56	52	51	51	51	51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	128888
5°	117686
10°	85419
15°	48633
20°	29788
25°	24013
30°	19592
35°	15740
40°	12452
45°	9830
50°	7684
55°	6021
60°	4791
65°	3853
70°	2805
75°	1483
80°	1105
85°	566

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 9830 cd/sqm



TEST NUMBER: P641207

CATALOG NUMBER: ML5612LSNFL2597FS1E - 694WB - 600LM - 3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	184.4	19.2
10°-20°	246.8	25.8
20°-30°	182.9	19.1
30°-40°	147.7	15.4
40°-50°	98.8	10.3
50°-60°	57.4	6.0
60°-70°	30.0	3.1
70°-80°	8.8	0.9
80°-90°	1.2	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	614.0	64.1
0°-40°	761.7	79.5
0°-60°	917.9	95.8
0°-90°	957.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	957.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2351	
5°	2139	184
15°	857	247
25°	397	183
35°	235	148
45°	127	99
55°	63	57
65°	30	30
75°	7	9
85°	1	1
90°	0	



TEST NUMBER: P641207

CATALOG NUMBER: ML5612LSNFL2597FS1E - 694WB - 600LM - 3000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	2351.1
2.5°	2302.1
5°	2138.6
7.5°	1865.8
10°	1534.5
12.5°	1182.1
15°	856.9
17.5°	634.8
20°	510.6
22.5°	445.0
25°	397.0
27.5°	351.5
30°	309.5
32.5°	271.0
35°	235.2
37.5°	202.8
40°	174.0
42.5°	149.5
45°	126.8
47.5°	106.7
50°	90.1
52.5°	75.2
55°	63.0
57.5°	52.5
60°	43.7
62.5°	36.7
65°	29.7
67.5°	24.5
70°	17.5
72.5°	11.4
75°	7.0
77.5°	4.4
80°	3.5
82.5°	1.7
85°	0.9
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)