

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P641347

Luminaire Tested: ML5612LSVWFL7597FS1E - 593WB - 900LM - 3000K

Issue Date: 2/17/2023

**Test Information**

Test Method: LM-79-2019  
Report Number: P641347  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-74)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/17/2023  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: HALO  
Catalog Number: ML5612LSVWFL7597FS1E - 593WB - 900LM - 3000K  
Description: ML56 RR, 75D TIR OPTIC, 5" WHITE BAFFLE TRIM  
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 3000K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1207.5 lumens  
Efficiency: N/A  
Efficacy: 90.8 lumens/watt  
Spacing Criteria (0/90/45): 1.19 / 1.19 / 1.09  
Luminous Opening: Circular (Dia: 0.42' x H: 0')  
CIE Type: Direct


Input Watts (W): 13.3  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



TEST NUMBER: P641347

CATALOG NUMBER: ML5612LSVWFL7597FS1E - 593WB - 900LM - 3000K

### Luminous Intensity Polar Plot





TEST NUMBER: P641347

CATALOG NUMBER: ML5612LSVWFL7597FS1E - 593WB - 900LM - 3000K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	113	110	107	104	110	107	105	103	103	101	99	100	98	96	96	95	94	92			92
2	106	101	96	92	104	99	95	91	96	92	89	93	90	87	90	88	85	84			84
3	100	93	87	83	98	91	86	82	89	84	81	86	82	79	84	81	78	76			76
4	94	85	79	74	92	84	78	74	82	77	73	80	76	72	78	74	71	70			70
5	88	79	72	68	87	78	72	67	76	71	67	74	70	66	73	69	65	64			64
6	83	73	66	62	82	72	66	61	71	65	61	69	64	61	68	64	60	59			59
7	78	68	61	57	77	67	61	56	66	60	56	65	60	56	64	59	55	54			54
8	74	63	57	52	73	63	56	52	62	56	52	61	55	51	60	55	51	50			50
9	70	59	53	48	69	59	52	48	58	52	48	57	51	48	56	51	48	46			46
10	66	55	49	45	65	55	49	45	54	48	44	53	48	44	52	48	44	43			43

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	65639
5°	66690
10°	68632
15°	71257
20°	72297
25°	68810
30°	61884
35°	49852
40°	33883
45°	17539
50°	10746
55°	7102
60°	3537
65°	2092
70°	2077
75°	2044
80°	2046
85°	1993

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 17539 cd/sqm



TEST NUMBER: P641347

CATALOG NUMBER: ML5612LSVWFL7597FS1E - 593WB - 900LM - 3000K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	80.8	6.7
10°-20°	245.9	20.4
20°-30°	359.8	29.8
30°-40°	317.3	26.3
40°-50°	134.4	11.1
50°-60°	46.7	3.9
60°-70°	13.0	1.1
70°-80°	7.1	0.6
80°-90°	2.4	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	686.5	56.9
0°-40°	1003.8	83.1
0°-60°	1184.9	98.1
0°-90°	1207.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1207.5	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	832	
5°	842	81
15°	872	246
25°	790	360
35°	517	317
45°	157	134
55°	52	47
65°	11	13
75°	7	7
85°	2	2
90°	0	



TEST NUMBER: P641347

CATALOG NUMBER: ML5612LSVWFL7597FS1E - 593WB - 900LM - 3000K

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	831.5
2.5°	834.8
5°	841.6
7.5°	849.4
10°	856.2
12.5°	865.1
15°	871.9
17.5°	873.0
20°	860.6
22.5°	831.5
25°	790.0
27.5°	739.5
30°	678.9
32.5°	604.8
35°	517.3
37.5°	421.9
40°	328.8
42.5°	233.4
45°	157.1
47.5°	108.8
50°	87.5
52.5°	67.3
55°	51.6
57.5°	37.0
60°	22.4
62.5°	15.7
65°	11.2
67.5°	10.1
70°	9.0
72.5°	7.9
75°	6.7
77.5°	5.6
80°	4.5
82.5°	3.4
85°	2.2
87.5°	1.1
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)