

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P641368

Luminaire Tested: ML5612LSVWFL7597FS1E - 594TBZB - 1200LM - 3500K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P641368
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-80)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5612LSVWFL7597FS1E - 594TBZB - 1200LM - 3500K
Description: ML56 RR, 75D TIR OPTIC, 5" TUSCON BRONZE GIMBAL TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1528.1 lumens
Efficiency: N/A
Efficacy: 92.6 lumens/watt
Spacing Criteria (0/90/45): 1.19 / 1.19 / 1.09
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct

Input Watts (W): 16.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P641368
CATALOG NUMBER: ML5612LSVWFL7597FS1E - 594TBZB - 1200LM - 3500K

Luminous Intensity Polar Plot





TEST NUMBER: P641368

CATALOG NUMBER: ML5612LSVWFL7597FS1E - 594TBZB - 1200LM - 3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	112	109	106	104	110	107	104	102	103	101	99	99	98	96	96	94	93	91			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	84	83			
3	99	92	86	81	97	90	85	80	87	83	79	85	81	78	83	79	77	75			
4	93	84	78	73	91	83	77	72	81	76	72	79	74	71	77	73	70	68			
5	87	78	71	66	86	77	70	66	75	69	65	73	68	64	71	67	64	62			
6	82	72	65	60	81	71	64	60	69	64	59	68	63	59	67	62	58	57			
7	77	67	60	55	76	66	59	55	65	59	54	63	58	54	62	57	54	52			
8	73	62	55	50	72	61	55	50	60	54	50	59	54	50	58	53	50	48			
9	69	58	51	47	68	57	51	47	56	50	46	55	50	46	54	50	46	44			
10	65	54	48	43	64	54	47	43	53	47	43	52	47	43	51	46	43	41			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	79328
5°	80629
10°	83237
15°	86580
20°	87703
25°	83644
30°	75065
35°	60394
40°	41715
45°	24929
50°	15769
55°	10763
60°	8368
65°	6780
70°	5470
75°	4270
80°	2546
85°	1268

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 24929 cd/sqm



TEST NUMBER: P641368

CATALOG NUMBER: ML5612LSVWFL7597FS1E - 594TBZB - 1200LM - 3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	97.8	6.4
10°-20°	298.4	19.5
20°-30°	437.0	28.6
30°-40°	385.2	25.2
40°-50°	183.0	12.0
50°-60°	73.6	4.8
60°-70°	36.4	2.4
70°-80°	14.9	1.0
80°-90°	1.9	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	833.2	54.5
0°-40°	1218.3	79.7
0°-60°	1474.9	96.5
0°-90°	1528.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1528.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1005	
5°	1018	98
15°	1059	298
25°	960	437
35°	627	385
45°	223	183
55°	78	74
65°	36	36
75°	14	15
85°	1	2
90°	0	



TEST NUMBER: P641368

CATALOG NUMBER: ML5612LSVWFL7597FS1E - 594TBZB - 1200LM - 3500K

CANDELA DISTRIBUTION (FULL):

0°	
0°	1004.9
2.5°	1009.1
5°	1017.5
7.5°	1027.3
10°	1038.4
12.5°	1048.2
15°	1059.4
17.5°	1059.4
20°	1044.0
22.5°	1009.1
25°	960.3
27.5°	898.9
30°	823.5
32.5°	731.4
35°	626.7
37.5°	513.6
40°	404.8
42.5°	304.3
45°	223.3
47.5°	166.1
50°	128.4
52.5°	97.7
55°	78.2
57.5°	64.2
60°	53.0
62.5°	43.3
65°	36.3
67.5°	29.3
70°	23.7
72.5°	18.1
75°	14.0
77.5°	9.8
80°	5.6
82.5°	2.8
85°	1.4
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)