

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P641381

Luminaire Tested: ML5612LSVWFL7597FS1E - 594WB - 1200LM - 2700K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P641381
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-78)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5612LSVWFL7597FS1E - 594WB - 1200LM - 2700K
Description: ML56 RR, 75D TIR OPTIC, 5" WHITE GIMBAL TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1452.8 lumens
Efficiency: N/A
Efficacy: 88.0 lumens/watt
Spacing Criteria (0/90/45): 1.19 / 1.19 / 1.09
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct


Input Watts (W): 16.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P641381

CATALOG NUMBER: ML5612LSVWFL7597FS1E - 594WB - 1200LM - 2700K

Luminous Intensity Polar Plot





TEST NUMBER: P641381

CATALOG NUMBER: ML5612LSVWFL7597FS1E - 594WB - 1200LM - 2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	104	110	107	104	102	103	101	99	99	98	96	96	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	84	83																			
3	99	92	86	81	97	90	85	80	87	83	79	85	81	78	83	79	77	75																			
4	93	84	78	73	91	83	77	72	81	76	71	79	74	71	77	73	70	68																			
5	87	78	71	66	86	77	70	66	75	69	65	73	68	64	71	67	64	62																			
6	82	72	65	60	81	71	64	60	69	64	59	68	63	59	67	62	58	57																			
7	77	67	60	55	76	66	59	55	65	59	54	63	58	54	62	57	54	52																			
8	73	62	55	50	72	61	55	50	60	54	50	59	54	50	58	53	50	48																			
9	69	58	51	47	68	57	51	46	56	50	46	55	50	46	54	50	46	44																			
10	65	54	48	43	64	54	47	43	53	47	43	52	47	43	51	46	43	41																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	75452
5°	76683
10°	79053
15°	82216
20°	83402
25°	79341
30°	71364
35°	57378
40°	39592
45°	23578
50°	14921
55°	10363
60°	7926
65°	6407
70°	5170
75°	4026
80°	2409
85°	1177

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 23578 cd/sqm



TEST NUMBER: P641381

CATALOG NUMBER: ML5612LSVWFL7597FS1E - 594WB - 1200LM - 2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	93.0	6.4
10°-20°	283.6	19.5
20°-30°	415.1	28.6
30°-40°	366.4	25.2
40°-50°	173.7	12.0
50°-60°	70.2	4.8
60°-70°	35.0	2.4
70°-80°	14.1	1.0
80°-90°	1.8	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	791.6	54.5
0°-40°	1158.0	79.7
0°-60°	1401.9	96.5
0°-90°	1452.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1452.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	956	
5°	968	93
15°	1006	284
25°	911	415
35°	595	366
45°	211	174
55°	75	70
65°	34	35
75°	13	14
85°	1	2
90°	0	



TEST NUMBER: P641381

CATALOG NUMBER: ML5612LSVWFL7597FS1E - 594WB - 1200LM - 2700K

CANDELA DISTRIBUTION (FULL):

	0°
0°	955.8
2.5°	959.8
5°	967.7
7.5°	976.9
10°	986.2
12.5°	996.7
15°	1006.0
17.5°	1007.3
20°	992.8
22.5°	958.4
25°	910.9
27.5°	854.2
30°	782.9
32.5°	695.7
35°	595.4
37.5°	489.8
40°	384.2
42.5°	289.1
45°	211.2
47.5°	158.4
50°	121.5
52.5°	93.7
55°	75.3
57.5°	60.7
60°	50.2
62.5°	42.2
65°	34.3
67.5°	29.0
70°	22.4
72.5°	17.2
75°	13.2
77.5°	9.2
80°	5.3
82.5°	2.6
85°	1.3
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)