

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P641633

Luminaire Tested: ML5612LSVWFL97FS1E - 592W - 900LM - 3500K

Issue Date: 2/17/2023

**Test Information**

Test Method: LM-79-2019  
Report Number: P641633  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-96)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/17/2023  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: HALO  
Catalog Number: ML5612LSVWFL97FS1E - 592W - 900LM - 3500K  
Description: ML56 RR, MILKY OPTIC, 5" WHITE TRIM  
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 3500K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1123.8 lumens  
Efficiency: N/A  
Efficacy: 84.5 lumens/watt  
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.14  
Luminous Opening: Circular (Dia: 0.5' x H: 0')  
CIE Type: Direct


Input Watts (W): 13.3  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



TEST NUMBER: P641633

CATALOG NUMBER: ML5612LSVWFL97FS1E - 592W - 900LM - 3500K

### Luminous Intensity Polar Plot





TEST NUMBER: P641633

CATALOG NUMBER: ML5612LSVWFL97FS1E - 592W - 900LM - 3500K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	111	107	104	101	109	105	102	99	101	99	96	97	95	93	94	92	91	89																			
2	103	97	91	87	101	95	90	86	92	88	84	89	85	82	86	83	80	78																			
3	96	88	81	76	94	86	80	75	83	78	74	81	76	73	78	75	71	70																			
4	90	80	72	67	87	78	72	66	76	70	66	74	69	65	72	68	64	62																			
5	84	73	65	60	82	72	65	59	70	64	59	68	62	58	66	61	58	56																			
6	78	67	59	54	76	66	59	53	64	58	53	63	57	53	61	56	52	50																			
7	73	61	54	49	72	61	54	48	59	53	48	58	52	48	57	52	48	46																			
8	69	57	49	44	67	56	49	44	55	49	44	54	48	44	53	47	44	42																			
9	65	53	46	41	63	52	45	41	51	45	40	50	44	40	49	44	40	38																			
10	61	49	42	37	60	49	42	37	48	41	37	47	41	37	46	41	37	35																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	36455
5°	36336
10°	35927
15°	35318
20°	34624
25°	33879
30°	32537
35°	29386
40°	23422
45°	16622
50°	12085
55°	9366
60°	8091
65°	7472
70°	7020
75°	6587
80°	5809
85°	4340

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 16622 cd/sqm



TEST NUMBER: P641633

CATALOG NUMBER: ML5612LSVWFL97FS1E - 592W - 900LM - 3500K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	62.5	5.6
10°-20°	175.4	15.6
20°-30°	256.9	22.9
30°-40°	269.2	24.0
40°-50°	170.2	15.1
50°-60°	91.1	8.1
60°-70°	57.3	5.1
70°-80°	32.8	2.9
80°-90°	8.5	0.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	494.8	44.0
0°-40°	764.0	68.0
0°-60°	1025.3	91.2
0°-90°	1123.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1123.8	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	665	
5°	660	63
15°	622	175
25°	560	257
35°	439	269
45°	214	170
55°	98	91
65°	58	57
75°	31	33
85°	7	8
90°	0	



TEST NUMBER: P641633

CATALOG NUMBER: ML5612LSVWFL97FS1E - 592W - 900LM - 3500K

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	665.0
2.5°	663.8
5°	660.3
7.5°	653.4
10°	645.4
12.5°	635.0
15°	622.3
17.5°	608.5
20°	593.5
22.5°	576.2
25°	560.1
27.5°	539.3
30°	514.0
32.5°	481.7
35°	439.1
37.5°	387.2
40°	327.3
42.5°	267.4
45°	214.4
47.5°	172.9
50°	141.7
52.5°	117.5
55°	98.0
57.5°	85.3
60°	73.8
62.5°	64.5
65°	57.6
67.5°	50.7
70°	43.8
72.5°	38.0
75°	31.1
77.5°	24.2
80°	18.4
82.5°	12.7
85°	6.9
87.5°	2.3
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)