

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P641646

Luminaire Tested: ML5612LSVWFL97FS1E - 593BB - 900LM - 2700K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P641646
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-98)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5612LSVWFL97FS1E - 593BB - 900LM - 2700K
Description: ML56 RR, MILKY OPTIC, 5" BLACK BAFFLE TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 759.9 lumens
Efficiency: N/A
Efficacy: 57.1 lumens/watt
Spacing Criteria (0/90/45): 1.14 / 1.14 / 1.11
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct


Input Watts (W): 13.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P641646

CATALOG NUMBER: ML5612LSVWFL97FS1E - 593BB - 900LM - 2700K

Luminous Intensity Polar Plot





TEST NUMBER: P641646

CATALOG NUMBER: ML5612LSVWFL97FS1E - 593BB - 900LM - 2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100																
1	113	110	107	104	110	108	105	103	103	101	100	100	98	97	96	95	94	92			92																
2	106	101	96	92	104	99	95	91	96	92	89	93	90	87	90	88	86	84			84																
3	100	93	87	82	98	91	86	82	88	84	80	86	82	79	84	81	78	76			76																
4	94	85	79	74	92	84	78	74	82	77	73	80	75	72	78	74	71	69			69																
5	88	79	72	67	86	78	71	67	76	70	66	74	69	65	72	68	65	63			63																
6	83	73	66	61	81	72	65	61	70	65	60	69	64	60	67	63	59	58			58																
7	78	67	60	56	76	67	60	56	65	59	55	64	59	55	63	58	55	53			53																
8	73	63	56	51	72	62	55	51	61	55	51	60	54	51	59	54	50	49			49																
9	69	58	52	47	68	58	51	47	57	51	47	56	50	47	55	50	46	45			45																
10	65	54	48	44	64	54	48	44	53	47	43	52	47	43	52	47	43	42			42																

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	29855
5°	29788
10°	29464
15°	28984
20°	28329
25°	27594
30°	26251
35°	23149
40°	17261
45°	10575
50°	5868
55°	2925
60°	1316
65°	428
70°	176
75°	233
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 10575 cd/sqm



TEST NUMBER: P641646

CATALOG NUMBER: ML5612LSVWFL97FS1E - 593BB - 900LM - 2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	51.3	6.7
10°-20°	143.8	18.9
20°-30°	209.1	27.5
30°-40°	210.8	27.7
40°-50°	109.3	14.4
50°-60°	30.4	4.0
60°-70°	4.5	0.6
70°-80°	0.7	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	404.1	53.2
0°-40°	614.9	80.9
0°-60°	754.6	99.3
0°-90°	759.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	759.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	545	
5°	541	51
15°	511	144
25°	456	209
35°	346	211
45°	136	109
55°	31	30
65°	3	5
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P641646

CATALOG NUMBER: ML5612LSVWFL97FS1E - 593BB - 900LM - 2700K

CANDELA DISTRIBUTION (FULL):

0°	
0°	544.6
2.5°	543.5
5°	541.3
7.5°	535.8
10°	529.3
12.5°	520.6
15°	510.7
17.5°	498.7
20°	485.6
22.5°	471.5
25°	456.2
27.5°	437.6
30°	414.7
32.5°	385.2
35°	345.9
37.5°	296.8
40°	241.2
42.5°	184.4
45°	136.4
47.5°	98.2
50°	68.8
52.5°	46.9
55°	30.6
57.5°	19.6
60°	12.0
62.5°	6.5
65°	3.3
67.5°	2.2
70°	1.1
72.5°	1.1
75°	1.1
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)