

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P641670

Luminaire Tested: ML5612LSVWFL97FS1E - 593TBZB - 1200LM - 5000K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P641670
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-100)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5612LSVWFL97FS1E - 593TBZB - 1200LM - 5000K
Description: ML56 RR, MILKY OPTIC, 5" TUSCON BRONZE BAFFLE TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1102.5 lumens
Efficiency: N/A
Efficacy: 66.8 lumens/watt
Spacing Criteria (0/90/45): 1.15 / 1.15 / 1.12
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct

Input Watts (W): 16.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P641670
CATALOG NUMBER: ML5612LSVWFL97FS1E - 593TBZB - 1200LM - 5000K

Luminous Intensity Polar Plot





TEST NUMBER: P641670

CATALOG NUMBER: ML5612LSVWFL97FS1E - 593TBZB - 1200LM - 5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	113	110	107	104	110	107	105	103	103	101	100	100	98	97	96	95	94	92			92
2	106	101	96	92	104	99	95	91	96	92	89	92	90	87	90	87	85	84			84
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76			76
4	94	85	79	74	92	84	78	73	81	76	72	79	75	71	77	74	71	69			69
5	88	78	72	67	86	77	71	66	75	70	66	74	69	65	72	68	64	63			63
6	83	72	65	61	81	71	65	60	70	64	60	68	63	59	67	62	59	57			57
7	78	67	60	55	76	66	60	55	65	59	55	64	58	54	62	58	54	53			53
8	73	62	55	51	72	62	55	51	60	55	50	59	54	50	58	53	50	48			48
9	69	58	51	47	68	57	51	47	56	51	46	55	50	46	55	50	46	45			45
10	65	54	48	43	64	54	47	43	53	47	43	52	47	43	51	46	43	41			41

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	61566
5°	61326
10°	60584
15°	59684
20°	58570
25°	57200
30°	54382
35°	47934
40°	35923
45°	22317
50°	12735
55°	6826
60°	3316
65°	1401
70°	692
75°	458
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 22317 cd/sqm



TEST NUMBER: P641670

CATALOG NUMBER: ML5612LSVWFL97FS1E - 593TBZB - 1200LM - 5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	73.3	6.6
10°-20°	205.8	18.7
20°-30°	300.8	27.3
30°-40°	303.6	27.5
40°-50°	160.2	14.5
50°-60°	48.0	4.4
60°-70°	9.2	0.8
70°-80°	1.6	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	579.9	52.6
0°-40°	883.5	80.1
0°-60°	1091.7	99.0
0°-90°	1102.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1102.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	780	
5°	774	73
15°	730	206
25°	657	301
35°	497	304
45°	200	160
55°	50	48
65°	8	9
75°	2	2
85°	0	0
90°	0	



TEST NUMBER: P641670

CATALOG NUMBER: ML5612LSVWFL97FS1E - 593TBZB - 1200LM - 5000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	779.9
2.5°	778.4
5°	773.9
7.5°	766.4
10°	755.8
12.5°	743.8
15°	730.3
17.5°	715.3
20°	697.2
22.5°	677.7
25°	656.7
27.5°	629.6
30°	596.6
32.5°	554.5
35°	497.4
37.5°	428.3
40°	348.6
42.5°	269.0
45°	199.9
47.5°	145.8
50°	103.7
52.5°	72.1
55°	49.6
57.5°	33.1
60°	21.0
62.5°	13.5
65°	7.5
67.5°	4.5
70°	3.0
72.5°	1.5
75°	1.5
77.5°	1.5
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)